



Mitraset Classic 19"

housing

Enclosure for housing electronic devices in a 19-inch rack

Product description

- Protection against mechanical stresses such as shocks, impacts, and vibrations. Optional protection against electromagnetic interference.
- IP 65 rated
- Protection against environmental factors such as heat, moisture, moisture, and dust.
- For loads up to 100 kg. Higher loads must be evaluated on a case-by-case basis.
- 3–16 height units (HU), nominal depth (ND) 219–762 mm.
- Housings with nominal depths 219 mm, 350 mm and 480 mm can be stacked together.
- Elastically susp. anti-vibration frame.
- Stacking segments on housing top and bottom.
- Recesses on side walls for drop handles.
- Recess also suitable for accommodating protective pressure compensation valves and humidity indicator.
- Lid with toggle-action snap fasteners.
- ZARGES Comfort Handles for ergonomic handling.
- Fulfils the requirements of VG 95447.
- Tested according to AECTP standards.
- Tested according to MIL-STD-810.
- Significantly better shielding properties compared to plastic enclosures. If necessary, these can be





further improved through special measures.

- Custom modifications are available.
- Made in Germany

Hints and special features

Also available as UN-approved hazardous goods packaging.

A comprehensive range of special equipment for a wide variety of applications.

Product variants

	45702	45708	45714	45726	45720	45732
Installation height	3 HE/U	4 HE/U	5 HE/U	7 HE/U	6 HE/U	8 HE/U
Nominal depth	219 mm	219 mm	219 mm	219 mm	219 mm	219 mm
Outside dimensions max. L x W x H	303 mm x 534 mm x 214,5 mm	303 mm x 534 mm x 259 mm	303 mm x 534 mm x 303,5 mm	303 mm x 534 mm x 392,5 mm	303 mm x 534 mm x 348 mm	303 mm x 534 mm x 437 mm
Weight	6.6 kg	7 kg	7.3 kg	7.8 kg	7.5 kg	8.2 kg

	45738	45744	45750	45756	45704	45710
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	3 HE/U	4 HE/U
Nominal depth	219 mm	219 mm	219 mm	219 mm	350 mm	350 mm
Outside dimensions max. L x W x H	303 mm x 534 mm x 481,5 mm	303 mm x 534 mm x 526 mm	303 mm x 534 mm x 570,5 mm	303 mm x 534 mm x 615 mm	434 mm x 534 mm x 214,5 mm	434 mm x 534 mm x 259 mm
Weight	8.4 kg	8.6 kg	8.8 kg	9 kg	8.6 kg	9 kg

	45716	45722	45728	45734	45740	45746
Installation height	5 HE/U	6 HE/U	7 HE/U	8 HE/U	9 HE/U	10 HE/U
Nominal depth	350 mm	350 mm	350 mm	350 mm	350 mm	350 mm
Outside dimensions max. L x W x H	434 mm x 534 mm x 303,5 mm	434 mm x 534 mm x 348 mm	434 mm x 534 mm x 348 mm	434 mm x 534 mm x 437 mm	434 mm x 534 mm x 481,5 mm	434 mm x 534 mm x 526 mm




	45716	45722	45728	45734	45740	45746
Weight	9.3 kg	9.6 kg	10 kg	10.3 kg	10.7 kg	11 kg

	45752	45758	45706	45712	45718	45724
Installation height	11 HE/U	12 HE/U	3 HE/U	4 HE/U	5 HE/U	6 HE/U
Nominal depth	350 mm	350 mm	480 mm	480 mm	480 mm	480 mm
Outside dimensions max. L x W x H	434 mm x 534 mm x 570,5 mm	434 mm x 534 mm x 615 mm	564 mm x 534 mm x 214,5 mm	564 mm x 534 mm x 259 mm	564 mm x 534 mm x 303,5 mm	564 mm x 534 mm x 348 mm
Weight	11.3 kg	11.6 kg	10.7 kg	11.1 kg	11.4 kg	11.9 kg

	45730	45736	45742	45748	45754	45760
Installation height	7 HE/U	8 HE/U	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Nominal depth	480 mm	480 mm	480 mm	480 mm	480 mm	480 mm
Outside dimensions max. L x W x H	564 mm x 534 mm x 392,5 mm	564 mm x 534 mm x 437 mm	564 mm x 534 mm x 481,5 mm	564 mm x 534 mm x 526 mm	564 mm x 534 mm x 570,5 mm	564 mm x 534 mm x 615 mm
Weight	12.2 kg	12.6 kg	13 kg	13.3 kg	13.7 kg	14.1 kg

	45803	45804	45805	45806	45807	45808
Installation height	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Nominal depth	610 mm	610 mm	610 mm	610 mm	610 mm	610 mm
Outside dimensions max. L x W x H	704 mm x 534 mm x 214,5 mm	704 mm x 534 mm x 259 mm	704 mm x 534 mm x 303,5 mm	704 mm x 534 mm x 348 mm	704 mm x 534 mm x 392,5 mm	704 mm x 534 mm x 437 mm
Weight	13.5 kg	14.1 kg	14.7 kg	15.2 kg	15.9 kg	16.6 kg

	45809	45810	45811	45812	45814	45816
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	14 HE/U	16 HE/U
Nominal depth	610 mm	610 mm	610 mm	610 mm	610 mm	610 mm
Outside dimensions max. L x W x H	704 mm x 534 mm x 481,5 mm	704 mm x 534 mm x 526 mm	704 mm x 534 mm x 570,5 mm	704 mm x 534 mm x 615 mm	704 mm x 534 mm x 704 mm	704 mm x 534 mm x 793 mm
Weight	17.1 kg	17.5 kg	24.7 kg	18.6 kg	19.9 kg	-



	45863	45864	45865	45866	45867	45868
Installation height	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Nominal depth	762 mm	762 mm	762 mm	762 mm	762 mm	762 mm
Outside dimensions max. L x W x H	856 mm x 534 mm x 214,5 mm	856 mm x 534 mm x 259 mm	856 mm x 534 mm x 303,5 mm	856 mm x 534 mm x 348 mm	856 mm x 534 mm x 392,5 mm	856 mm x 534 mm x 437 mm
Weight	16.2 kg	16.8 kg	17.4 kg	17.9 kg	18.6 kg	19.3 kg

	45869	45870	45871	45872	45874	45876
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	14 HE/U	16 HE/U
Nominal depth	762 mm	762 mm	762 mm	762 mm	762 mm	762 mm
Outside dimensions max. L x W x H	856 mm x 534 mm x 481,5 mm	856 mm x 534 mm x 526 mm	856 mm x 534 mm x 570,5 mm	856 mm x 534 mm x 615 mm	856 mm x 534 mm x 704 mm	856 mm x 534 mm x 793 mm
Weight	19.8 kg	20.2 kg	20.8 kg	21.3 kg	22 kg	23.8 kg

	45878
Installation height	18 HE/U
Nominal depth	762 mm
Outside dimensions max. L x W x H	856 mm x 534 mm x 882 mm
Weight	25.6 kg

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:
 sales@zarges.co.uk

www.zarges.com/uk

Effective 14/5/2026
 Subject to change or error.