



# Lid for Mitraset Racklite

## 19" housing

### Product description

- Flexible stacking elements at the corners of the housing and lid. Units with the same nominal depth are stackable.
- Lid equipped with 4 locking catches.
- Lid with ribbing for reinforcement.
- Protection class IP 65 in accordance with DIN EN 6060529 and IEC 34-5/529 through seam-welded housing and lid with peripheral seal.
- Wide range of special lids available on request.



### Product variants

	45933	45934	45935	45936	45937	45938
Height of lid	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Outside dimensions max. L x W x H	55 mm x 591 mm x 271,5 mm	55 mm x 591 mm x 316 mm	55 mm x 591 mm x 360,5 mm	55 mm x 591 mm x 405 mm	55 mm x 591 mm x 449,5 mm	55 mm x 591 mm x 494 mm
Weight	2.2 kg	2.4 kg	2.6 kg	2.7 kg	2.9 kg	3.1 kg

	45939	45940	45941	45942
Height of lid	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Outside dimensions max. L x W x H	55 mm x 591 mm x 538,5 mm	55 mm x 591 mm x 583 mm	55 mm x 591 mm x 627,5 mm	55 mm x 591 mm x 672 mm
Weight	3.3 kg	3.4 kg	3.6 kg	3.8 kg



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 26/6/2026  
Subject to change or error.