DATA SHEET

Lid for Mitraset Racklite 19" housing

PRODUCT DESCRIPTION

- Flexible stacking elements at the corners of the housing and lid. Units with the same nominal depth are stackable.
- Lid equipped with 4 locking catches.
- Lid with ribbing for reinforcement.
- Protection class IP 65 in accordance with DIN EN 60 60529 and IEC 34-5/529 through seam-welded housing and lid with peripheral seal.
- Wide range of special lids available on request.



PRODUCT VARIANTS

	45933	45934	45935	45936	45937	45938
Height of lid	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Outside dimensions max. L x W x H	55 mm × 591 mm × 271,5 mm	55 mm × 591 mm × 316 mm	55 mm × 591 mm × 360,5 mm	55 mm × 591 mm × 405 mm	55 mm × 591 mm × 449,5 mm	55 mm × 591 mm × 494 mm
Weight	2.2 kg	2.4 kg	2.6 kg	2.7 kg	2.9 kg	3.1 kg

	45939	45940	45941	45942
Height of lid	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Outside dimensions max. L x W x H	55 mm × 591 mm × 538,5 mm	55 mm × 591 mm × 583 mm	55 mm × 591 mm × 627,5 mm	55 mm × 591 mm × 672 mm
Weight	3.3 kg	3.4 kg	3.6 kg	3.8 kg

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 10/11/2026
Subject to change or error.