



# Mitraset Racklite Basic 19" housing

Enclosure for housing electronic devices in a 19-inch rack

## Product description

- For mounting electronic devices in a 19-inch rack
- A range of designs with various nominal depths and height units.
- A comprehensive range of special equipment for a wide variety of applications.
- Protection class IP 65 in accordance with DIN EN 6060529 and IEC 34-5/529 through seam-welded housing and lid with peripheral seal.
- The anti-vibration frame is connected to the housing via 8 rubber dampers and 2 earth straps.
- Stackable using stacking knobs and recesses.
- Items with same nominal depth are stackable.
- ZARGES Comfort Handles for ergonomic handling.
- ZARGES Comfort fastener for ergonomic use and an extremely long service life.
- Equipped with snap fasteners with protection against accidental opening.
- RF-tight version is available as special equipment.



## Product variants



	45943	45944	45945	45946	45947	45948
Installation height	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Nominal depth	350 mm	350 mm	350 mm	350 mm	350 mm	350 mm
Outside dimensions max. L x W x H	456 mm x 568 mm x 226 mm	456 mm x 568 mm x 270,5 mm	456 mm x 568 mm x 315 mm	456 mm x 568 mm x 359,5 mm	456 mm x 568 mm x 404 mm	456 mm x 568 mm x 448,5 mm
Weight	7.7 kg	8.3 kg	8.7 kg	9 kg	9.3 kg	9.6 kg

	45949	45950	45951	45952	45953	45954
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	3 HE/U	4 HE/U
Nominal depth	350 mm	350 mm	350 mm	350 mm	480 mm	480 mm
Outside dimensions max. L x W x H	456 mm x 568 mm x 493 mm	456 mm x 568 mm x 537,5 mm	456 mm x 568 mm x 582 mm	456 mm x 568 mm x 626,5 mm	586 mm x 568 mm x 226 mm	586 mm x 568 mm x 270,5 mm
Weight	10 kg	10.3 kg	10.6 kg	11 kg	9.1 kg	9.8 kg

	45955	45956	45957	45958	45959	45960
Installation height	5 HE/U	6 HE/U	7 HE/U	8 HE/U	9 HE/U	10 HE/U
Nominal depth	480 mm	480 mm	480 mm	480 mm	480 mm	480 mm
Outside dimensions max. L x W x H	586 mm x 568 mm x 315 mm	586 mm x 568 mm x 359,5 mm	586 mm x 568 mm x 404 mm	586 mm x 568 mm x 448,5 mm	586 mm x 568 mm x 493 mm	586 mm x 568 mm x 537,5 mm
Weight	10.2 kg	10.5 kg	10.5 kg	11.3 kg	11.7 kg	12 kg

	45961	45962	45963	45964	45965	45966
Installation height	11 HE/U	12 HE/U	3 HE/U	4 HE/U	5 HE/U	6 HE/U
Nominal depth	480 mm	480 mm	610 mm	610 mm	610 mm	610 mm
Outside dimensions max. L x W x H	586 mm x 568 mm x 582 mm	586 mm x 568 mm x 626,5 mm	716 mm x 568 mm x 226 mm	716 mm x 568 mm x 270,5 mm	716 mm x 568 mm x 315 mm	716 mm x 568 mm x 359,5 mm
Weight	12.4 kg	12.8 kg	10.4 kg	11.1 kg	11.5 kg	11.9 kg



	45967	45968	45969	45970	45971	45972
Installation height	7 HE/U	8 HE/U	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Nominal depth	610 mm	610 mm	610 mm	610 mm	610 mm	610 mm
Outside dimensions max. L x W x H	716 mm x 568 mm x 404 mm	716 mm x 568 mm x 448,5 mm	716 mm x 568 mm x 493 mm	716 mm x 568 mm x 537,5 mm	716 mm x 568 mm x 582 mm	716 mm x 568 mm x 626,5 mm
Weight	12.3 kg	12.8 kg	13.2 kg	13.6 kg	14 kg	14.4 kg

	45973	45974	45975	45976	45977	45978
Installation height	-	-	-	-	-	-
Nominal depth	-	-	-	-	-	-
Outside dimensions max. L x W x H	-	-	-	-	-	-
Weight	-	-	-	-	-	-

	45979	45980	45981	45982
Installation height	-	-	-	-
Nominal depth	-	-	-	-
Outside dimensions max. L x W x H	-	-	-	-
Weight	-	-	-	-

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 12/5/2026

Subject to change or error.