



Lid for Mitraset Racklite

Basic 19" housing

Product description

- Protection class IP 65 in accordance with DIN EN 6060529 and IEC 34-5/529 through seam-welded housing and lid with peripheral seal.
- Wide range of special lids available on request.
- Lid with ribbing for reinforcement.
- Lid equipped with 4 locking catches.

Product variants

	45983	45984	45985	45986	45987	45988
Height of lid	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Outside dimensions max. L x W x H	40 mm x 568 mm x 226 mm	40 mm x 568 mm x 270,5 mm	40 mm x 568 mm x 315 mm	40 mm x 568 mm x 359,5 mm	40 mm x 568 mm x 404 mm	40 mm x 568 mm x 448,5 mm
Weight	1.8 kg	2 kg	2.2 kg	2.3 kg	2.5 kg	2.7 kg

	45989	45990	45991	45992
Height of lid	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Outside dimensions max. L x W x H	40 mm x 568 mm x 493 mm	40 mm x 568 mm x 537,5 mm	40 mm x 568 mm x 582 mm	40 mm x 568 mm x 626,5 mm
Weight	2.9 kg	3 kg	3.2 kg	3.4 kg

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway

CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 26/6/2026

Subject to change or error.