

K 470 universal case, IP 65

For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.

Product description

- For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.
- Protection class IP 65 in accordance with EN 60 529 through foamed seal in the lid.
- 3 standard sizes ex stock, customised versions available on request.
- Also available with approval for the transportation of hazardous goods.
- Extra thick 1.5-mm sheet metal for all K 470 containers from basic dimensions of 750 x 550 mm.
- Automatic pressure compensation membrane
- Leak-tightness verified with TÜV SÜD certificate.
- Available for most K 470 models.




Hints and special features

UN approval for the transportation of hazardous goods possible at additional charge.

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

Product features



Colour of the stacking corners Natural aluminium	Corner beading Yes	Fasteners Comfort fasteners	Integrated wheels No	Material Aluminium
Material of the stacking corners Aluminium	Number of handles 2	Peripheral beading Yes	Protection class IP65:	Seal foamed lid seal
Stacking corners Yes	Warranty 10 years			

Product variants

SKU 366206	SKU 366217	SKU 366218
Internal dimensions L x W x H 550 mm × 350 mm × 380 mm	Internal dimensions L x W x H 750 mm × 550 mm × 380 mm	Internal dimensions L x W x H 750 mm × 550 mm × 580 mm
Max. gross weight dangerous goods permission 75 kg	Max. gross weight dangerous goods permission 102 kg	Max. gross weight dangerous goods permission 126 kg
Outside dimensions max. L x W x H 600 mm × 400 mm × 410 mm	Outside dimensions max. L x W x H 800 mm × 600 mm × 410 mm	Outside dimensions max. L x W x H 800 mm × 600 mm × 610 mm
Volume 73 l	Volume 157 l	Volume 239 l
Weight 5.3 kg	Weight 10 kg	Weight 12 kg