



# Alto L

The compact alternative - with respect to size, weight and price/performance ratio.

## Product description

- The compact alternative - with respect to size, weight and price/performance ratio.
- Very light but still extremely stable.
- Rung depth: 30 mm
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>	Pitch rung/tread <b>270 mm</b>
Standards <b>EN 131 professional</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	

## Product variants

SKU <b>41547</b>	SKU <b>41548</b>	SKU <b>41550</b>
Number of rungs <b>7</b>	Number of rungs <b>8</b>	Number of rungs <b>10</b>
Overall length	Overall length	Overall length



<b>2.21 m</b>	<b>2.49 m</b>	<b>3.05 m</b>
Stile depth <b>58 mm</b>	Stile depth <b>58 mm</b>	Stile depth <b>58 mm</b>
Transport dimensions <b>2.210 mm × 350 mm × 60 mm</b>	Transport dimensions <b>2.490 mm × 350 mm × 60 mm</b>	Transport dimensions <b>3.050 mm × 350 mm × 60 mm</b>
Weight <b>4 kg</b>	Weight <b>4.4 kg</b>	Weight <b>6.1 kg</b>
Working height <b>3.05 m</b>	Working height <b>3.35 m</b>	Wide crosspiece <b>0.79 m</b>
		Working height <b>3.9 m</b>
SKU <b>41552</b>	SKU <b>41554</b>	SKU <b>41556</b>
Number of rungs <b>12</b>	Number of rungs <b>14</b>	Number of rungs <b>16</b>
Overall length <b>3.61 m</b>	Overall length <b>4.17 m</b>	Overall length <b>4.73 m</b>
Stile depth <b>58 mm</b>	Stile depth <b>68 mm</b>	Stile depth <b>68 mm</b>
Transport dimensions <b>3.610 mm × 350 mm × 60 mm</b>	Transport dimensions <b>4.170 mm × 350 mm × 65 mm</b>	Transport dimensions <b>4.730 mm × 350 mm × 70 mm</b>
Weight <b>7 kg</b>	Weight <b>8 kg</b>	Weight <b>9.2 kg</b>
Wide crosspiece <b>0.79 m</b>	Wide crosspiece <b>0.79 m</b>	Wide crosspiece <b>0.89 m</b>
Working height <b>4.4 m</b>	Working height <b>4.95 m</b>	Working height <b>5.5 m</b>



SKU <b>41558</b>	SKU <b>41560</b>	SKU <b>41562</b>
Number of rungs <b>18</b>	Number of rungs <b>20</b>	Number of rungs <b>22</b>
Overall length <b>5.29 m</b>	Overall length <b>5.85 m</b>	Overall length <b>6.41 m</b>
Stile depth <b>73 mm</b>	Stile depth <b>73 mm</b>	Stile depth <b>85 mm</b>
Transport dimensions <b>5.290 mm × 350 mm × 80 mm</b>	Transport dimensions <b>5.850 mm × 350 mm × 80 mm</b>	Transport dimensions <b>6.410 mm × 350 mm × 80 mm</b>
Weight <b>10.5 kg</b>	Weight <b>11.5 kg</b>	Weight <b>13.2 kg</b>
Wide crosspiece <b>0.89 m</b>	Wide crosspiece <b>0.99 m</b>	Wide crosspiece <b>0.99 m</b>
Working height <b>6.05 m</b>	Working height <b>6.6 m</b>	Working height <b>7.15 m</b>
SKU <b>41564</b>		
Number of rungs <b>24</b>		
Overall length <b>6.98 m</b>		
Stile depth <b>85 mm</b>		
Transport dimensions <b>6.970 mm × 350 mm × 90 mm</b>		
Weight <b>14.4 kg</b>		



Wide crosspiece

**1.1 m**

Working height

**7.7 m**