



## Alto L

The compact alternative—in terms of both size and weight, as well as price/performance.

### Product description

- The compact alternative—in terms of both size and weight, as well as price/performance.
- Very lightweight but extremely stable.
- Rung depth 30 mm.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from aluminium extrusions.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	aluminium
Standards	EN 131 professional
Tread depth	30 mm
Type of rungs/treads	serrated



Vertical distance between each rung/tread	270 mm
Warranty	10 years

## Product variants

	41547	41548	41550	41552	41554	41556
Number of rungs	7	8	10	12	14	16
Overall length	2.21 m	2.49 m	3.05 m	3.61 m	4.17 m	4.73 m
Stile depth	58 mm	58 mm	58 mm	58 mm	68 mm	68 mm
Transport dimensions	2.210 mm × 350 mm × 60 mm	2.490 mm × 350 mm × 60 mm	3.050 mm × 350 mm × 60 mm	3.610 mm × 350 mm × 60 mm	4.170 mm × 350 mm × 65 mm	4.730 mm × 350 mm × 70 mm
Weight	4 kg	4.4 kg	6.1 kg	7 kg	8 kg	9.2 kg
Wide crosspiece	–	–	0.79 m	0.79 m	0.79 m	0.89 m
Working height	3.05 m	3.35 m	3.9 m	4.4 m	4.95 m	5.5 m

	41558	41560	41562	41564
Number of rungs	18	20	22	24
Overall length	5.29 m	5.85 m	6.41 m	6.98 m
Stile depth	73 mm	73 mm	85 mm	85 mm
Transport dimensions	5.290 mm × 350 mm × 80 mm	5.850 mm × 350 mm × 80 mm	6.410 mm × 350 mm × 80 mm	6.970 mm × 350 mm × 90 mm
Weight	10.5 kg	11.5 kg	13.2 kg	14.4 kg
Wide crosspiece	0.89 m	0.99 m	0.99 m	1.1 m
Working height	6.05 m	6.6 m	7.15 m	7.7 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
 sales@zarges.co.uk

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 9/6/2026  
 Subject to change or error.