



Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	External width of lower ladder 420 mm	Load capacity max. 150 kg	Material aluminium



Standards EN 131 professional	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/ tread 265 mm	Warranty 10 years
certification-mark-pf TÜV-SÜD				

Product variants

SKU 44834	SKU 44820	SKU 44822
Number of rungs 2 × 8	Number of rungs 2 × 10	Number of rungs 2 × 12
Overall length, extended 3.8 m	Overall length, extended 4.93 m	Overall length, extended 6.05 m
Overall length, retracted 2.42 m	Overall length, retracted 2.98 m	Overall length, retracted 3.54 m
Stile depth 58 mm	Stile depth 68 mm	Stile depth 68 mm
Transport dimensions 2.420 mm × 420 mm × 115 mm	Transport dimensions 2.980 mm × 430 mm × 120 mm	Transport dimensions 3.540 mm × 430 mm × 135 mm
Weight 9.3 kg	Weight 11.3 kg	Weight 15.4 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m
Working height 4.6 m	Working height 5.65 m	Working height 6.8 m



SKU	SKU	SKU
44824	44826	44828
Number of rungs	Number of rungs	Number of rungs
2 × 14	2 × 16	2 × 18
Overall length, extended	Overall length, extended	Overall length, extended
7.17 m	8.29 m	9.17 m
Overall length, retracted	Overall length, retracted	Overall length, retracted
4.1 m	4.66 m	5.23 m
Stile depth	Stile depth	Stile depth
85 mm	85 mm	85 mm
Transport dimensions	Transport dimensions	Transport dimensions
4.100 mm × 430 mm × 135 mm	4.660 mm × 430 mm × 145 mm	5.230 mm × 430 mm × 145 mm
Weight	Weight	Weight
17.8 kg	21.5 kg	23.9 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
1.1 m	1.2 m	1.2 m
Working height	Working height	Working height
7.85 m	8.7 m	9.8 m