



Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 420 mm	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 265 mm	Standards EN 131 professional	Tread depth 38 mm	Type rung/tread serrated	Warranty 10 years

Product variants

SKU	SKU	SKU
-----	-----	-----



44834	44820	44822
Number of rungs 2 × 8	Number of rungs 2 × 10	Number of rungs 2 × 12
Overall length, extended 3.8 m	Overall length, extended 4.93 m	Overall length, extended 6.05 m
Overall length, retracted 2.42 m	Overall length, retracted 2.98 m	Overall length, retracted 3.54 m
Stile depth 58 mm	Stile depth 68 mm	Stile depth 68 mm
Transport dimensions 2.420 mm × 420 mm × 115 mm	Transport dimensions 2.980 mm × 430 mm × 120 mm	Transport dimensions 3.540 mm × 430 mm × 135 mm
Weight 9.3 kg	Weight 11.3 kg	Weight 15.4 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m
Working height 4.6 m	Working height 5.65 m	Working height 6.8 m
SKU 44824	SKU 44826	SKU 44828
Number of rungs 2 × 14	Number of rungs 2 × 16	Number of rungs 2 × 18
Overall length, extended 7.17 m	Overall length, extended 8.29 m	Overall length, extended 9.17 m
Overall length, retracted 4.1 m	Overall length, retracted 4.66 m	Overall length, retracted 5.23 m
Stile depth 85 mm	Stile depth 85 mm	Stile depth 85 mm



Transport dimensions 4.100 mm × 430 mm × 135 mm	Transport dimensions 4.660 mm × 430 mm × 145 mm	Transport dimensions 5.230 mm × 430 mm × 145 mm
Weight 17.8 kg	Weight 21.5 kg	Weight 23.9 kg
Wide crosspiece 1.1 m	Wide crosspiece 1.2 m	Wide crosspiece 1.2 m
Working height 7.85 m	Working height 8.7 m	Working height 9.8 m