



Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged
External width of lower ladder	420 mm



Load capacity	max. 150 kg
Material	aluminium
Standards	EN 131 professional
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years

Product variants

	44834	44820	44822	44824	44826	44828
Number of rungs	2 × 8	2 × 10	2 × 12	2 × 14	2 × 16	2 × 18
Overall length, extended	3.8 m	4.93 m	6.05 m	7.17 m	8.29 m	9.17 m
Overall length, retracted	2.42 m	2.98 m	3.54 m	4.1 m	4.66 m	5.23 m
Stile depth	58 mm	68 mm	68 mm	85 mm	85 mm	85 mm
Transport dimensions	2.420 mm × 420 mm × 115 mm	2.980 mm × 430 mm × 120 mm	3.540 mm × 430 mm × 135 mm	4.100 mm × 430 mm × 135 mm	4.660 mm × 430 mm × 145 mm	5.230 mm × 430 mm × 145 mm
Weight	9.3 kg	11.3 kg	15.4 kg	17.8 kg	21.5 kg	23.9 kg
Wide crosspiece	0.8 m	0.9 m	1 m	1.1 m	1.2 m	1.2 m
Working height	4.6 m	5.65 m	6.8 m	7.85 m	8.7 m	9.8 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 18/5/2026

Subject to change or error.