



# Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

## Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Outside width of lower ladder: 420 mm.
- Positive guide fittings of aluminium extruded section.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	External width of lower ladder <b>420 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>aluminium</b>



Standards <b>EN 131 professional</b>	Tread depth <b>38 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/ tread <b>265 mm</b>	Warranty <b>10 years</b>
certification-mark-pf <b>TÜV-SÜD</b>				

## Product variants

SKU <b>44834</b>	SKU <b>44820</b>	SKU <b>44822</b>
Number of rungs <b>2 × 8</b>	Number of rungs <b>2 × 10</b>	Number of rungs <b>2 × 12</b>
Overall length, extended <b>3.8 m</b>	Overall length, extended <b>4.93 m</b>	Overall length, extended <b>6.05 m</b>
Overall length, retracted <b>2.42 m</b>	Overall length, retracted <b>2.98 m</b>	Overall length, retracted <b>3.54 m</b>
Stile depth <b>58 mm</b>	Stile depth <b>68 mm</b>	Stile depth <b>68 mm</b>
Transport dimensions <b>2.420 mm × 420 mm × 115 mm</b>	Transport dimensions <b>2.980 mm × 430 mm × 120 mm</b>	Transport dimensions <b>3.540 mm × 430 mm × 135 mm</b>
Weight <b>9.3 kg</b>	Weight <b>11.3 kg</b>	Weight <b>15.4 kg</b>
Wide crosspiece <b>0.8 m</b>	Wide crosspiece <b>0.9 m</b>	Wide crosspiece <b>1 m</b>
Working height <b>4.6 m</b>	Working height <b>5.65 m</b>	Working height <b>6.8 m</b>



SKU	SKU	SKU
<b>44824</b>	<b>44826</b>	<b>44828</b>
Number of rungs	Number of rungs	Number of rungs
<b>2 × 14</b>	<b>2 × 16</b>	<b>2 × 18</b>
Overall length, extended	Overall length, extended	Overall length, extended
<b>7.17 m</b>	<b>8.29 m</b>	<b>9.17 m</b>
Overall length, retracted	Overall length, retracted	Overall length, retracted
<b>4.1 m</b>	<b>4.66 m</b>	<b>5.23 m</b>
Stile depth	Stile depth	Stile depth
<b>85 mm</b>	<b>85 mm</b>	<b>85 mm</b>
Transport dimensions	Transport dimensions	Transport dimensions
<b>4.100 mm × 430 mm × 135 mm</b>	<b>4.660 mm × 430 mm × 145 mm</b>	<b>5.230 mm × 430 mm × 145 mm</b>
Weight	Weight	Weight
<b>17.8 kg</b>	<b>21.5 kg</b>	<b>23.9 kg</b>
Wide crosspiece	Wide crosspiece	Wide crosspiece
<b>1.1 m</b>	<b>1.2 m</b>	<b>1.2 m</b>
Working height	Working height	Working height
<b>7.85 m</b>	<b>8.7 m</b>	<b>9.8 m</b>