
DATA SHEET

Megastep S

Extreme strength meets maximum height: 250 kg load capacity with industry-leading working height for the most demanding applications.















PRODUCT DESCRIPTION

- Extreme strength meets maximum height: 250 kg load capacity with industry-leading working height for the most demanding applications.
- A sturdy platform that provides a secure footing even during extended periods of work.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Clean hands thanks to wear-resistant, anodised black styles.
- 5 rungs or more: High-strength polyester webbing with sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable two-component plastic end caps that attach securely to the stile and prevent the ladder from slipping.
- Robust design: flanged rung-stile connection with a platform and extruded aluminum profiles.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value

Property	Value
Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 250 kg
Material	aluminium
Platform length	250 mm
Platform width	250 mm
Standards	EN 131 professional
Stile depth	73 mm
Stile depth	58 mm
Stile depth steps/back stay	73mm / 58mm
Storage tray	aluminium
Tread depth	60 mm
Type of rungs/treads	SL Step
Vertical distance between each rung/tread	265 mm
Warranty	10 years

PRODUCT VARIANTS


	41145	41146	41147	41148	41149
Anti-splay mechanism	–	–	Belt strap	Belt strap	Belt strap
Base	0,76 m × 0,44 m	0,93 m × 0,47 m	1,1 m × 0,5 m	1,27 m × 0,53 m	1,61 m × 0,59 m
No. of rungs incl. platform	3	4	5	6	8
Overall base width	0.44 m	0.47 m	0.5 m	0.53 m	0.59 m
Overall length	1.59 m	1.87 m	2.15 m	2.43 m	2.99 m
Platform height	0.8 m	1.06 m	1.33 m	1.59 m	2.12 m
Transport dimensions	1.595 mm × 445 mm × 150 mm	1.875 mm × 475 mm × 150 mm	2.155 mm × 505 mm × 150 mm	2.435 mm × 535 mm × 150 mm	2.995 mm × 595 mm × 150 mm
Weight	6.2 kg	7.3 kg	8 kg	8.6 kg	9.6 kg
Working height	2.8 m	3.1 m	3.35 m	3.6 m	4.15 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 6



Ground spikes
SKU 40939



Pivot foot with rubber tread 100 x 55 mm
SKU 40997



Pivot foot with rubber tread 125 x 50 mm
SKU 40226



Stile extension
SKU 40922



Tension strap
SKU 40960



Theft protection
SKU 8210

SPARE PARTS 6




Bracing
SKU 820816



Plug-in end cap
SKU 824350 · 824352



Push-on end cap, antistatic
SKU 824475 · 824476



Splay prevention (belt strap)
SKU 827885 · 827675



Storage tray
SKU 829798



User instructions label
SKU 800609

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 10/11/2026
Subject to change or error.