



XLstep S

Light weight and easy to handle, as well as great value.

Product description

- Light weight and easy to handle, as well as great value.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon straps prevent splay, from 4 treads.
- Triple-riveted connection between rung and stile.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features



Coating anodised	Connection between stiles and rungs/stiles riveted	Load capacity max. 150 kg	Material aluminium	Platform length 250 mm
Platform width 300 mm	Standards EN 131 professional	Stile depth 42 mm	Storage tray aluminium	Tread depth 80 mm
Type of rungs/treads serrated	Vertical distance between each rung/ tread 250 mm	Warranty 10 years	certification-mark-pf TÜV-SÜD	

Product variants

SKU 41223	SKU 41224	SKU 41225
Base 0,74 m × 0,49 m	Anti-splay mechanism Belt strap	Anti-splay mechanism Belt strap
Number of rungs, incl. platform 3	Base 0,91 m × 0,52 m	Base 1,08 m × 0,55 m
Overall base width 0.49 m	Number of rungs, incl. platform 4	Number of rungs, incl. platform 5
Overall length 1.56 m	Overall base width 0.52 m	Overall base width 0.55 m
Platform height 0.74 m	Overall length 1.83 m	Overall length 2.1 m
Stile depth 42 mm	Platform height 0.99 m	Platform height 1.24 m
Stile depth steps/back stay	Stile depth	Stile depth



42mm / 42mm	42 mm	42 mm
Transport dimensions approx. 1.560 mm × approx. 490 mm × approx. 155 mm	Stile depth steps/back stay 42mm / 42mm	Stile depth steps/back stay 42mm / 42mm
Vertical ladder height 1.42 m	Transport dimensions approx. 1.830 mm × approx. 520 mm × approx. 155 mm	Transport dimensions approx. 2.100 mm × approx. 550 mm × approx. 155 mm
Weight 6 kg	Vertical ladder height 1.67 m	Vertical ladder height 1.92 m
Working height 2.75 m	Weight 6.9 kg	Weight 7.7 kg
	Working height 3 m	Working height 3.25 m
SKU 41226	SKU 41227	SKU 41228
Anti-splay mechanism Belt strap	Anti-splay mechanism Belt strap	Anti-splay mechanism Belt strap
Base 1,25 m × 0,57 m	Base 1,42 m × 0,61 m	Base 1,59 m × 0,63 m
Number of rungs, incl. platform 6	Number of rungs, incl. platform 7	Number of rungs, incl. platform 8
Overall base width 0.57 m	Overall base width 0.61 m	Overall base width 0.63 m
Overall length 2.37 m	Overall length 2.64 m	Overall length 2.91 m
Platform height	Platform height	Platform height



1.49 m	1.74 m	1.99 m
Stile depth	Stile depth	Stile depth
48 mm	48 mm	48 mm
Stile depth steps/back stay	Stile depth steps/back stay	Stile depth steps/back stay
48mm / 42mm	48mm / 42mm	48mm / 42mm
Transport dimensions	Transport dimensions	Transport dimensions
approx. 2.370 mm × approx. 570 mm × approx. 155 mm	approx. 2.640 mm × approx. 610 mm × approx. 155 mm	approx. 2.910 mm × approx. 630 mm × approx. 155 mm
Vertical ladder height	Vertical ladder height	Vertical ladder height
2.17 m	2.42 m	2.67 m
Weight	Weight	Weight
9.1 kg	10.2 kg	11.7 kg
Working height	Working height	Working height
3.5 m	3.75 m	4 m
SKU		
41230		
Anti-splay mechanism		
Belt strap		
Base		
1,93 m × 0,69 m		
Number of rungs, incl. platform		
10		
Overall base width		
0.69 m		
Overall length		



3.45 m

Platform height

2.49 m

Stile depth

48 mm

Stile depth steps/back stay

48mm / 42mm

Transport dimensions

approx. 3.450 mm × approx. 690 mm × approx. 155 mm

Vertical ladder height

3.17 m

Weight

14.1 kg

Working height

4.5 m