



XLstep S

Designed for frequent relocation: lightweight and durable, with a wide platform, a storage tray, and sturdy ladder end caps.

Product description

- Designed for frequent relocation: lightweight and durable, with a wide platform, a storage tray, and sturdy ladder end caps.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Non-slip two-component ladder feet with a large contact surface.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Clean hands thanks to wear-resistant anodised stiles.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- Easy access up and down via sturdy 80-mm-deep treads.
- Triple-riveted connection between rung and stile.
- 4 treads and up: High-strength polyester webbing with sewn-in attachment tabs – durable and resistant to wear and tear.
- Sturdy design for daily use: platform and profiles made of extruded aluminum.



Hints and special features



Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	aluminium
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	42 mm
Storage tray	aluminium
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Warranty	10 years

Product variants

	41223	41224	41225	41226	41227	41228
Anti-splay mechanism	–	Belt strap	Belt strap	Belt strap	Belt strap	Belt strap
Base	0,75 m × 0,5 m	0,92 m × 0,53 m	1,08 m × 0,56 m	1,26 m × 0,59 m	1,43 m × 0,62 m	1,6 m × 0,65 m
Number of rungs, incl. platform	3	4	5	6	7	8
Overall base width	0.5 m	0.53 m	0.56 m	0.59 m	0.62 m	0.65 m



	41223	41224	41225	41226	41227	41228
Overall length	1.56 m	1.83 m	2.1 m	2.37 m	2.64 m	2.91 m
Platform height	0.74 m	0.99 m	1.24 m	1.49 m	1.74 m	1.99 m
Stile depth	42 mm	42 mm	42 mm	48 mm	48 mm	48 mm
Stile depth steps/back stay	42mm / 42mm	42mm / 42mm	42mm / 42mm	48mm / 42mm	48mm / 42mm	48mm / 42mm
Transport dimensions	approx. 1.560 mm × approx. 500 mm × approx. 155 mm	approx. 1.830 mm × approx. 530 mm × approx. 155 mm	approx. 2.100 mm × approx. 560 mm × approx. 155 mm	approx. 2.370 mm × approx. 590 mm × approx. 155 mm	approx. 2.640 mm × approx. 620 mm × approx. 155 mm	approx. 2.910 mm × approx. 650 mm × approx. 155 mm
Vertical ladder height	1.42 m	1.67 m	1.92 m	2.17 m	2.42 m	2.67 m
Weight	6 kg	6.9 kg	7.7 kg	9.1 kg	10.2 kg	11.7 kg
Working height	2.75 m	3 m	3.25 m	3.5 m	3.75 m	4 m

	41230
Anti-splay mechanism	Belt strap
Base	1,94 m × 0,7 m
Number of rungs, incl. platform	10
Overall base width	0.7 m
Overall length	3.45 m
Platform height	2.49 m
Stile depth	48 mm
Stile depth steps/back stay	48mm / 42mm
Transport dimensions	approx. 3.450 mm × approx. 700 mm × approx. 155 mm
Vertical ladder height	3.17 m
Weight	14.1 kg
Working height	4.5 m



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 1/7/2026
Subject to change or error.