



EFAmix S

The solution for work in an electrical environment.

Product description

- The solution for work in an electrical environment.
- Suitable for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Meets the requirements of the high-voltage test for ladders made of insulating material in accordance with DIN EN 61 478.
- Aluminium treads, 80 mm deep, with non-slip ribbing.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in plastic storage tray.
- Only 88 mm wide when folded.
- Treads made of aluminium extrusion.



Hints and special features

Complies with EN 131 Professional.

Product features

Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic
Platform length	250 mm
Platform width	250 mm



Standards EN 131 professional

Stile depth	50 mm
Stile depth	50 mm
Stile depth steps/back stay	50mm / 50mm
Storage tray	Plastic
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	230 mm
Warranty	10 years

Product variants

	40431	40432	40433	40434	40435
Base	0,75 m × 0,52 m	0,91 m × 0,55 m	1,07 m × 0,57 m	1,24 m × 0,6 m	1,4 m × 0,62 m
Number of rungs, incl. platform	3	4	5	6	7
Overall base width	0.52 m	0.55 m	0.57 m	0.6 m	0.62 m
Overall length	1.4 m	1.65 m	1.9 m	2.15 m	2.4 m
Platform height	0.68 m	0.91 m	1.14 m	1.37 m	1.6 m
Transport dimensions	1.390 mm × approx. 520 mm × 100 mm	1.640 mm × approx. 550 mm × 100 mm	1.890 mm × approx. 570 mm × 100 mm	2.140 mm × approx. 600 mm × 100 mm	2.390 mm × approx. 620 mm × 100 mm
Weight	6 kg	7 kg	8 kg	9 kg	10 kg
Working height	2.7 m	2.9 m	3.15 m	3.35 m	3.6 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
 sales@zarges.co.uk

www.zarges.com/uk

Effective 30/5/2026
 Subject to change or error.