



EFAmix S

The solution for work in an electrical environment.

Product description

- The solution for work in an electrical environment.
- Suitable for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Meets the requirements of the high-voltage test for ladders made of insulating material in accordance with DIN EN 61 478.
- Aluminium treads, 80 mm deep, with non-slip ribbing.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in plastic storage tray.
- Only 88 mm wide when folded.
- Treads made of aluminium extrusion.



Hints and special features

Complies with EN 131 Professional.

Product features

Connection between stiles and rungs/stiles flanged	Load capacity max. 150 kg	Material Aluminium / plastic	Platform length 250 mm	Platform width 250 mm
Standards EN 131 professional	Stile depth 50 mm	Stile depth 50 mm	Stile depth steps/back stay 50mm / 50mm	Storage tray Plastic



Tread depth 80 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 230 mm	Warranty 10 years
-----------------------------	---	--	-----------------------------

Product variants

SKU 40431	SKU 40432	SKU 40433
Base 0,75 m × 0,52 m	Base 0,91 m × 0,55 m	Base 1,07 m × 0,57 m
Number of rungs, incl. platform 3	Number of rungs, incl. platform 4	Number of rungs, incl. platform 5
Overall base width 0.52 m	Overall base width 0.55 m	Overall base width 0.57 m
Overall length 1.4 m	Overall length 1.65 m	Overall length 1.9 m
Platform height 0.68 m	Platform height 0.91 m	Platform height 1.14 m
Transport dimensions 1.390 mm × approx. 520 mm × 100 mm	Transport dimensions 1.640 mm × approx. 550 mm × 100 mm	Transport dimensions 1.890 mm × approx. 570 mm × 100 mm
Weight 6 kg	Weight 7 kg	Weight 8 kg
Working height 2.7 m	Working height 2.9 m	Working height 3.15 m



SKU	SKU
40434	40435
Base	Base
1,24 m × 0,6 m	1,4 m × 0,62 m
Number of rungs, incl. platform	Number of rungs, incl. platform
6	7
Overall base width	Overall base width
0.6 m	0.62 m
Overall length	Overall length
2.15 m	2.4 m
Platform height	Platform height
1.37 m	1.6 m
Transport dimensions	Transport dimensions
2.140 mm × approx. 600 mm × 100 mm	2.390 mm × approx. 620 mm × 100 mm
Weight	Weight
9 kg	10 kg
Working height	Working height
3.35 m	3.6 m