



EFAmix S

The special ladders for all applications in electrical environments.

Product description

- The special ladders for all applications in electrical environments.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Treads made from extruded aluminium section.



Hints and special features

Complies with EN 131 Professional.

Product features

Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium / plastic	Number of rungs, incl. platform 3	Overall base width 0.52 m



Overall length 1.4 m	Pitch rung/tread 230 mm	Platform height 0.68 m	Platform length 250 mm	Platform width 250 mm
Standards EN 131 professional	Stile depth 50 mm	Stile depth 50 mm	Stile depth steps/back stay 50mm / 50mm	Tray Plastic
Tread depth 80 mm	Type rung/tread serrated	Warranty 10 years	Weight 6 kg	Working height 2.7 m

Product variants

SKU 40431	SKU 40432	SKU 40433
Base 0,75 m × 0,52 m	Base 0,91 m × 0,55 m	Base 1,07 m × 0,57 m
Transport dimensions 1.390 mm × approx. 520 mm × 100 mm	Transport dimensions 1.640 mm × approx. 550 mm × 100 mm	Transport dimensions 1.890 mm × approx. 570 mm × 100 mm
SKU 40434	SKU 40435	
Base 1,24 m × 0,6 m	Base 1,4 m × 0,62 m	
Transport dimensions 2.140 mm × approx. 600 mm × 100 mm	Transport dimensions 2.390 mm × approx. 620 mm × 100 mm	