DATA SHEET

Skymaster X

Convertible to take on challenging tasks with greater safety.





PRODUCT DESCRIPTION

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged

Property	Value
Load capacity	max. 150 kg
Material	aluminium
Rigid locking bar	on one side
Standards	EN 131 professional
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years

PRODUCT VARIANTS

	41536	41537	41538	41539	41540	41542
Ladder length as 3-part single ladder	4.1 m	5 m	5.8 m	6.7 m	6.9 m	8.6 m
Length as 2-part single ladder and as stepladder with push-on section	3 m	3.6 m	4.1 m	4.7 m	4.95 m	6.1 m
Number of rungs	3 × 6	3 × 7	3 × 8	3 × 9	3 × 10	3 × 12
Overall length, retracted	1.9 m	2.2 m	2.45 m	2.7 m	3 m	3.55 m
Stile depth	68 mm	68 mm	73 mm	85 mm	85 mm	98 mm
Transport dimensions	1.880 mm × 500 mm × 180 mm	2.160 mm × 500 mm × 180 mm	2.440 mm × 500 mm × 200 mm	2.730 mm × 500 mm × 200 mm	3.010 mm × 500 mm × 210 mm	3.590 mm × 500 mm × 230 mm
Weight	13.8 kg	15 kg	17.5 kg	20 kg	25.2 kg	30.1 kg
Wide crosspiece	0.8 m	0.9 m	1 m	1.1 m	1.1 m	1.2 m
Working height as 3-part single ladder	5 m	5.8 m	6.65 m	7.45 m	7.7 m	9.35 m

	41544
Ladder length as 3-part single ladder	9.7 m
Length as 2-part single ladder and as stepladder with push-on section	6.95 m
Number of rungs	3 × 14
Overall length, retracted	4.15 m
Stile depth	98 mm
Transport dimensions	4.140 mm × 500 mm × 230 mm
Weight	37.9 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	10.4 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 9



Ground spikes
SKU 40939



Hanging hooks
SKU 40058 · 40059



Hook-on platform
SKU 40450



Stand-off bracket with tool tray
SKU 40100



Stile extension
SKU 40922



Stile extension for horizontal stabiliser bars
SKU 41989



Tension strap
SKU 40960



Theft protection
SKU 8210



Wall support / base stabiliser
SKU 40250

SPARE PARTS 17



Brace connector
SKU 860240



Brace retainer
SKU 800270



End cap
SKU 824162 · 824153



Guide fittings
SKU 826297 · 826260 · 826298 · +1



Horizontal stabiliser bar
SKU 823475 · 823981



Inclination-angle indicator
SKU 824369



Lift-off retainer
SKU 821382



Plug-in end cap
SKU 824302 · 824352 · 824353 · +1



Plug-in end cap, antistatic
SKU 824321 · 824323



Push-on end cap
SKU 824243



Push-on end cap, antistatic
SKU 824478



Rigid locking bar, aluminium, right
SKU 826793 · 826794 · 826795



Round buffer
SKU 824277



Rung hook
SKU 826148 · 826040



Rung slide piece
SKU 824732



Splay prevention (belt strap)
SKU 827494 · 827894 · 827895 · +2



User instructions label
SKU 800605

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 11/11/2026
Subject to change or error.