



Skymaster X

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	Load capacity max. 150 kg	Material aluminium	Rigid locking bar on one side
---------------------------	--	-------------------------------------	------------------------------	---



Standards	Tread depth	Type of rungs/treads	Vertical distance between each rung/tread	Warranty
EN 131 professional	30 mm	serrated	265 mm	10 years

Product variants

SKU	SKU	SKU
41536	41537	41538
Ladder length as 3-part single ladder	Ladder length as 3-part single ladder	Ladder length as 3-part single ladder
4.1 m	5 m	5.8 m
Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section
3 m	3.6 m	4.1 m
Number of rungs	Number of rungs	Number of rungs
3 × 6	3 × 7	3 × 8
Overall length, retracted	Overall length, retracted	Overall length, retracted
1.9 m	2.2 m	2.45 m
Stile depth	Stile depth	Stile depth
68 mm	68 mm	73 mm
Transport dimensions	Transport dimensions	Transport dimensions
1.880 mm × 500 mm × 180 mm	2.160 mm × 500 mm × 180 mm	2.440 mm × 500 mm × 200 mm
Weight	Weight	Weight
13.8 kg	15 kg	17.5 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
0.8 m	0.9 m	1 m
Working height as 3-part single ladder	Working height as 3-part single ladder	Working height as 3-part single ladder



5 m	5.8 m	6.65 m
SKU 41539	SKU 41540	SKU 41542
Ladder length as 3-part single ladder 6.7 m	Ladder length as 3-part single ladder 6.9 m	Ladder length as 3-part single ladder 8.6 m
Length as 2-part single ladder and as stepladder with push-on section 4.7 m	Length as 2-part single ladder and as stepladder with push-on section 4.95 m	Length as 2-part single ladder and as stepladder with push-on section 6.1 m
Number of rungs 3 × 9	Number of rungs 3 × 10	Number of rungs 3 × 12
Overall length, retracted 2.7 m	Overall length, retracted 3 m	Overall length, retracted 3.55 m
Stile depth 85 mm	Stile depth 85 mm	Stile depth 98 mm
Transport dimensions 2.730 mm × 500 mm × 200 mm	Transport dimensions 3.010 mm × 500 mm × 210 mm	Transport dimensions 3.590 mm × 500 mm × 230 mm
Weight 20 kg	Weight 25.2 kg	Weight 30.1 kg
Wide crosspiece 1.1 m	Wide crosspiece 1.1 m	Wide crosspiece 1.2 m
Working height as 3-part single ladder 7.45 m	Working height as 3-part single ladder 7.7 m	Working height as 3-part single ladder 9.35 m
SKU 41544		
Ladder length as 3-part single ladder		



9.7 m

Length as 2-part single ladder and as
stepladder with push-on section

6.95 m

Number of rungs

3 × 14

Overall length, retracted

4.15 m

Stile depth

98 mm

Transport dimensions

4.140 mm × 500 mm × 230 mm

Weight

37.9 kg

Wide crosspiece

1.2 m

Working height as 3-part single ladder

10.4 m