



Skymaster X

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 265 mm
Rigid locking bar on one side	Standards EN 131 professional	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years

Product variants



SKU 41536	SKU 41537	SKU 41538
Ladder length as 3-part single ladder 4.1 m	Ladder length as 3-part single ladder 5 m	Ladder length as 3-part single ladder 5.8 m
Length as 2-part single ladder and as stepladder with push-on section 3 m	Length as 2-part single ladder and as stepladder with push-on section 3.6 m	Length as 2-part single ladder and as stepladder with push-on section 4.1 m
Number of rungs 3 × 6	Number of rungs 3 × 7	Number of rungs 3 × 8
Overall length, retracted 1.9 m	Overall length, retracted 2.2 m	Overall length, retracted 2.45 m
Stile depth 68 mm	Stile depth 68 mm	Stile depth 73 mm
Transport dimensions 1.880 mm × 500 mm × 180 mm	Transport dimensions 2.160 mm × 500 mm × 180 mm	Transport dimensions 2.440 mm × 500 mm × 200 mm
Weight 13.8 kg	Weight 15 kg	Weight 17.5 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m
Working height as 3-part single ladder 5 m	Working height as 3-part single ladder 5.8 m	Working height as 3-part single ladder 6.65 m
SKU 41539	SKU 41540	SKU 41542
Ladder length as 3-part single ladder 6.7 m	Ladder length as 3-part single ladder 6.9 m	Ladder length as 3-part single ladder 8.6 m
Length as 2-part single ladder and as stepladder with push-on section 4.7 m	Length as 2-part single ladder and as stepladder with push-on section 4.95 m	Length as 2-part single ladder and as stepladder with push-on section 6.1 m
Number of rungs	Number of rungs	Number of rungs



3 x 9	3 x 10	3 x 12
Overall length, retracted 2.7 m	Overall length, retracted 3 m	Overall length, retracted 3.55 m
Stile depth 85 mm	Stile depth 85 mm	Stile depth 98 mm
Transport dimensions 2.730 mm x 500 mm x 200 mm	Transport dimensions 3.010 mm x 500 mm x 210 mm	Transport dimensions 3.590 mm x 500 mm x 230 mm
Weight 20 kg	Weight 25.2 kg	Weight 30.1 kg
Wide crosspiece 1.1 m	Wide crosspiece 1.1 m	Wide crosspiece 1.2 m
Working height as 3-part single ladder 7.45 m	Working height as 3-part single ladder 7.7 m	Working height as 3-part single ladder 9.35 m
SKU 41544		
Ladder length as 3-part single ladder 9.7 m		
Length as 2-part single ladder and as stepladder with push-on section 6.95 m		
Number of rungs 3 x 14		
Overall length, retracted 4.15 m		
Stile depth 98 mm		
Transport dimensions 4.140 mm x 500 mm x 230 mm		



Weight

37.9 kg

Wide crosspiece

1.2 m

Working height as 3-part single ladder

10.4 m