



Skymaster DX

Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.

Product description

- Probably the only ladder you'll ever need! Our best selling ladder offers unrivalled flexibility and durability.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection between stiles and rungs/stiles	Load capacity	Material	Standards
---------	--	---------------	----------	-----------



natural	flanged	max. 150 kg	aluminium	EN 131 professional
Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/ tread 265 mm	Warranty 10 years	

Product variants

SKU 44837	SKU 44838	SKU 44839
Ladder length as 3-part single ladder 4.4 m	Ladder length as 3-part single ladder 5.25 m	Ladder length as 3-part single ladder 6.1 m
Length as 2-part single ladder and as stepladder with push-on section 3.25 m	Length as 2-part single ladder and as stepladder with push-on section 3.85 m	Length as 2-part single ladder and as stepladder with push-on section 4.4 m
Number of rungs 3 × 7	Number of rungs 3 × 8	Number of rungs 3 × 9
Overall length, retracted 2.14 m	Overall length, retracted 2.42 m	Overall length, retracted 2.7 m
Stile depth 58 mm	Stile depth 68 mm	Stile depth 73 mm
Transport dimensions 2.130 mm × 500 mm × 170 mm	Transport dimensions 2.410 mm × 500 mm × 170 mm	Transport dimensions 2.690 mm × 500 mm × 190 mm
Weight 13.8 kg	Weight 16.3 kg	Weight 18 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m



Working height as 3-part single ladder 5.2 m	Working height as 3-part single ladder 6 m	Working height as 3-part single ladder 6.85 m
SKU 44840	SKU 44841	SKU 44842
Ladder length as 3-part single ladder 6.65 m	Ladder length as 3-part single ladder 7.2 m	Ladder length as 3-part single ladder 8.3 m
Length as 2-part single ladder and as stepladder with push-on section 4.65 m	Length as 2-part single ladder and as stepladder with push-on section 5.25 m	Length as 2-part single ladder and as stepladder with push-on section 5.8 m
Number of rungs 3 × 10	Number of rungs 3 × 11	Number of rungs 3 × 12
Overall length, retracted 2.98 m	Overall length, retracted 3.26 m	Overall length, retracted 3.54 m
Stile depth 73 mm	Stile depth 85 mm	Stile depth 85 mm
Transport dimensions 2.970 mm × 500 mm × 190 mm	Transport dimensions 3.270 mm × 500 mm × 200 mm	Transport dimensions 3.550 mm × 500 mm × 220 mm
Weight 20.5 kg	Weight 22.3 kg	Weight 25.9 kg
Wide crosspiece 1.1 m	Wide crosspiece 1.1 m	Wide crosspiece 1.2 m
Working height as 3-part single ladder 7.35 m	Working height as 3-part single ladder 7.9 m	Working height as 3-part single ladder 9 m
SKU 44844		



Ladder length as 3-part single ladder

9.45 m

Length as 2-part single ladder and as
stepladder with push-on section

6.654 m

Number of rungs

3 × 14

Overall length, retracted

4.1 m

Stile depth

98 mm

Transport dimensions

4.110 mm × 500 mm × 220 mm

Weight

31.5 kg

Wide crosspiece

1.2 m

Working height as 3-part single ladder

10.05 m