DATA SHEET

Skymaster DX

Functionality and flexibility with standard features and excellent price/performance.



PRODUCT DESCRIPTION

- Functionality and flexibility with standard features and excellent price/performance.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged

Property	Value
Load capacity	max. 150 kg
Material	aluminium
Standards	EN 131 professional
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years

PRODUCT VARIANTS

	44837	44838	44839	44840	44841	44842
Ladder length as 3-part single ladder	4.4 m	5.25 m	6.1 m	6.65 m	7.2 m	8.3 m
Length as 2-part single ladder and as stepladder with push-on section	3.25 m	3.85 m	4.4 m	4.65 m	5.25 m	5.8 m
Number of rungs	3 × 7	3 × 8	3 × 9	3 × 10	3 × 11	3 × 12
Overall length, retracted	2.14 m	2.42 m	2.7 m	2.98 m	3.26 m	3.54 m
Stile depth	58 mm	68 mm	73 mm	73 mm	85 mm	85 mm
Transport dimensions	2.130 mm × 500 mm × 170 mm	2.410 mm × 500 mm × 170 mm	2.690 mm × 500 mm × 190 mm	2.970 mm × 500 mm × 190 mm	3.270 mm × 500 mm × 200 mm	3.550 mm × 500 mm × 220 mm
Weight	13.8 kg	16.3 kg	18 kg	20.5 kg	22.3 kg	25.9 kg
Wide crosspiece	0.8 m	0.9 m	1 m	1.1 m	1.1 m	1.2 m
Working height as 3-part single ladder	5.2 m	6 m	6.85 m	7.35 m	7.9 m	9 m

	44844
Ladder length as 3-part single ladder	9.45 m
Length as 2-part single ladder and as stepladder with push-on section	6.654 m
Number of rungs	3 × 14
Overall length, retracted	4.1 m
Stile depth	98 mm
Transport dimensions	4.110 mm × 500 mm × 220 mm
Weight	31.5 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	10.05 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 5



Ground spikes
SKU 40939



Stile extension
SKU 40922



Stile extension for horizontal stabiliser bars
SKU 41987 · 41989



Tension strap
SKU 40960



Wall support / base stabiliser
SKU 40250

SPARE PARTS 9



End cap
SKU 824152 · 824153



Guide fitting
SKU 800352



Horizontal stabiliser bar
SKU 800492 · 800551 · 800549 · +1



Horizontal stabiliser bar
SKU 823981



Plug-in end cap
SKU 824350 · 824302 · 824352 · +2



Push-on end cap
SKU 824242 · 824243



Push-on end cap
SKU 800309



Splay prevention (belt strap)
SKU 800328 · 800337 · 800329 · +3



User instructions label
SKU 800605

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 12/11/2026
Subject to change or error.