



Combimaster DX

The inexpensive alternative for universal use as a extension ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	Coating	Connection between stiles and rungs/stiles	Load capacity	Material
1,64 m × 0,89 m	natural	flanged	max. 150 kg	aluminium



Standards	Tread depth	Type of rungs/treads	Vertical distance between each rung/tread	Warranty
EN 131 professional	38 mm	serrated	265 mm	10 years

Product variants

SKU	SKU	SKU
44868	44870	44872
Length as trestle	Length as trestle	Length as trestle
2.25 m	2.81 m	3.33 m
Number of rungs	Number of rungs	Number of rungs
2 × 8	2 × 10	2 × 12
Overall length, extended	Overall length, extended	Overall length, extended
3.82 m	4.94 m	6.06 m
Overall length, retracted	Overall length, retracted	Overall length, retracted
2.4 m	2.98 m	3.54 m
Stile depth	Stile depth	Stile depth
58 mm	68 mm	73 mm
Transport dimensions	Transport dimensions	Transport dimensions
2.400 mm × 420 mm × 120 mm	2.970 mm × 430 mm × 120 mm	3.530 mm × 430 mm × 130 mm
Weight	Weight	Weight
10 kg	12.3 kg	15.3 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
0.89 m	0.9 m	1 m
Working height	Working height	Working height



4.9 m	5.7 m	6.8 m
SKU		
44874		
Length as trestle		
3.86 m		
Number of rungs		
2 × 14		
Overall length, extended		
6.9 m		
Overall length, retracted		
4.1 m		
Stile depth		
85 mm		
Transport dimensions		
4.090 mm × 430 mm × 135 mm		
Weight		
18.2 kg		
Wide crosspiece		
1.1 m		
Working height		
7.6 m		