



Combimaster DX

The inexpensive alternative for universal use as a extension ladder and stepladder.

Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	Coating	Connection between stiles and rungs/stiles	Load capacity	Material
1,64 m × 0,89 m	natural	flanged	max. 150 kg	aluminium



Standards EN 131 professional	Tread depth 38 mm	Type of rungs/treads serrated	Vertical distance between each rung/ tread 265 mm	Warranty 10 years
certification-mark-pf TÜV-SÜD				

Product variants

SKU 44868	SKU 44870	SKU 44872
Length as trestle 2.25 m	Length as trestle 2.81 m	Length as trestle 3.33 m
Number of rungs 2 × 8	Number of rungs 2 × 10	Number of rungs 2 × 12
Overall length, extended 3.82 m	Overall length, extended 4.94 m	Overall length, extended 6.06 m
Overall length, retracted 2.4 m	Overall length, retracted 2.98 m	Overall length, retracted 3.54 m
Stile depth 58 mm	Stile depth 68 mm	Stile depth 73 mm
Transport dimensions 2.400 mm × 420 mm × 120 mm	Transport dimensions 2.970 mm × 430 mm × 120 mm	Transport dimensions 3.530 mm × 430 mm × 130 mm
Weight 10 kg	Weight 12.3 kg	Weight 15.3 kg
Wide crosspiece 0.89 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m



Working height	Working height	Working height
4.9 m	5.7 m	6.8 m
SKU		
44874		
Length as trestle		
3.86 m		
Number of rungs		
2 × 14		
Overall length, extended		
6.9 m		
Overall length, retracted		
4.1 m		
Stile depth		
85 mm		
Transport dimensions		
4.090 mm × 430 mm × 135 mm		
Weight		
18.2 kg		
Wide crosspiece		
1.1 m		
Working height		
7.6 m		