



# Combimaster DX

The inexpensive alternative for universal use as a extension ladder and stepladder.

## Product description

- The inexpensive alternative for universal use as a extension ladder and stepladder.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Can be used as a two-section push-up ladder or as a ladder with double-sided access.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- With cross-tube for stability.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of aluminium extruded sections for maximum safety.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Base	1,64 m × 0,89 m
Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged



Load capacity	max. 150 kg
Material	aluminium
Standards	EN 131 professional
Tread depth	38 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years

## Product variants

	44868	44870	44872	44874
Length as trestle	2.25 m	2.81 m	3.33 m	3.86 m
Number of rungs	2 × 8	2 × 10	2 × 12	2 × 14
Overall length, extended	3.82 m	4.94 m	6.06 m	6.9 m
Overall length, retracted	2.4 m	2.98 m	3.54 m	4.1 m
Stile depth	58 mm	68 mm	73 mm	85 mm
Transport dimensions	2.400 mm × 420 mm × 120 mm	2.970 mm × 430 mm × 120 mm	3.530 mm × 430 mm × 130 mm	4.090 mm × 430 mm × 135 mm
Weight	10 kg	12.3 kg	15.3 kg	18.2 kg
Wide crosspiece	0.89 m	0.9 m	1 m	1.1 m
Working height	4.9 m	5.7 m	6.8 m	7.6 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 26/6/2026  
 Subject to change or error.