



## AMA P

The modular solution for flexible or stationary application: extendible from a step stool to a complete work platform in various heights.

### Product description

- The modular solution for flexible or stationary application: extendible from a step stool to a complete work platform in various heights.
- Modular design for changing or expanding configurations at any time – can be used as a mobile or stationary work platform.
- Lightweight for quick and convenient handling.
- Extremely robust, torsion-resistant, corrosion-proof aluminium alloy structure.
- Two-step basic module with up to three add-on steps suitable for mobile applications.
- Wide range of accessories for stationary or mobile applications.
- Add-on modules in four different heights.
- Comfortable, safe steps (555 × 250 mm) made from serrated aluminium sheet.



### Hints and special features

Complies with EN 14 183

### Product features

Coating	Connection between stiles and rungs/stiles	Load capacity	Material	Platform length
---------	--	---------------	----------	-----------------



natural	welded	max. 150 kg	aluminium	250 mm
Platform width <b>555 mm</b>	Standards <b>EN 14183</b>	Tread depth <b>250 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/ tread  <b>200 mm</b>
Warranty  <b>10 years</b>				

## Product variants

SKU <b>40261</b>	SKU <b>40260</b>	SKU <b>40262</b>
Module combination <b>A</b>	Module combination <b>B</b>	Module combination <b>B + C</b>
Module, individual <b>Module A</b>	Module, individual <b>Module B</b>	Module, individual <b>Module C</b>
Overall platform depth <b>0.3 m</b>	Overall platform depth <b>0.55 m</b>	Overall platform depth <b>0.8 m</b>
Platform height <b>0.2 m</b>	Platform height <b>0.4 m</b>	Platform height <b>0.4 m</b>
Total max. weight <b>2.9 kg</b>	Total max. weight <b>4.8 kg</b>	Total max. weight <b>8.7 kg</b>
Transport dimensions <b>580 mm × 290 mm × 200 mm</b>	Transport dimensions <b>620 mm × 550 mm × 400 mm</b>	Transport dimensions <b>610 mm × 280 mm × 380 mm</b>
Weight <b>2.9 kg</b>	Weight <b>4.8 kg</b>	Weight <b>3.9 kg</b>



Working height <b>2.2 m</b>	Working height <b>2.4 m</b>	Working height <b>2.4 m</b>
SKU <b>40263</b>	SKU <b>40264</b>	SKU <b>40265</b>
Module combination <b>B + D</b>	Module combination <b>B + D + E</b>	Module combination <b>B + D + E + F</b>
Module, individual <b>Module D</b>	Module, individual <b>Module E</b>	Module, individual <b>Module F</b>
Overall platform depth <b>0.8 m</b>	Overall platform depth <b>1.05 m</b>	Overall platform depth <b>1.3 m</b>
Platform height <b>0.6 m</b>	Platform height <b>0.8 m</b>	Platform height <b>0.99 m</b>
Total max. weight <b>9.2 kg</b>	Total max. weight <b>14 kg</b>	Total max. weight <b>19.5 kg</b>
Transport dimensions <b>630 mm × 290 mm × 590 mm</b>	Transport dimensions <b>660 mm × 290 mm × 790 mm</b>	Transport dimensions <b>690 mm × 290 mm × 980 mm</b>
Weight <b>4.4 kg</b>	Weight <b>4.8 kg</b>	Weight <b>5.5 kg</b>
Working height <b>2.6 m</b>	Working height <b>2.8 m</b>	Working height <b>2.99 m</b>