



## AFA P

The basic steps with low weight, high stability and convenient standing area.

### Product description

- The basic steps with low weight, high stability and convenient standing area.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- 200 mm deep steps made of non-slip ribbed aluminium sheet.
- 350 x 577 mm standing platform braced by a cross-strut.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



### Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.

Complies with EN 14 183

### Product features

Coating	natural
Connection between stiles and rungs/stiles	welded
Load capacity	max. 150 kg
Material	aluminium



Platform length	350 mm
Platform width	577 mm
Standards	EN 14183
Tread depth	200 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	200 mm
Warranty	10 years

## Product variants

	40031	40032	40033	40034	40035
Base	0,4 m × 0,6 m	0,64 m × 0,67 m	0,87 m × 0,69 m	1,1 m × 0,71 m	1,35 m × 0,73 m
Number of rungs, incl. platform	1	2	3	4	5
Platform height	0.2 m	0.4 m	0.6 m	0.8 m	0.99 m
Transport dimensions	600 mm × 406 mm × 200 mm	671 mm × 639 mm × 400 mm	692 mm × 871 mm × 600 mm	713 mm × 1.103 mm × 800 mm	734 mm × 1.336 mm × 1.000 mm
Weight	3 kg	5.5 kg	7.8 kg	10.1 kg	13.5 kg
Working height	2.2 m	2.4 m	2.6 m	2.8 m	3 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.  
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 15/5/2026  
 Subject to change or error.