



AFA P

The basic steps with low weight, high stability and convenient standing area.

Product description

- The basic steps with low weight, high stability and convenient standing area.
- High-strength, welded tubular aluminium construction ensures stability and long service life.
- 200 mm deep steps made of non-slip ribbed aluminium sheet.
- 350 x 577 mm standing platform braced by a cross-strut.
- Maximum stability thanks to a wide standing surface.
- Stile ends with plastic edge finish.



Hints and special features

Self-locking sprung castors available as an accessory from two steps upwards. Handrail available as an accessory from three steps upwards.

Complies with EN 14 183

Product features

Coating natural	Connection between stiles and rungs/stiles welded	Load capacity max. 150 kg	Material aluminium	Platform length 350 mm
Platform width	Standards	Tread depth	Type of rungs/treads	Vertical distance between each rung/



577 mm	EN 14183	200 mm	serrated	tread 200 mm
Warranty 10 years				

Product variants

SKU 40031	SKU 40032	SKU 40033
Base 0,4 m × 0,6 m	Base 0,64 m × 0,67 m	Base 0,87 m × 0,69 m
Number of rungs, incl. platform 1	Number of rungs, incl. platform 2	Number of rungs, incl. platform 3
Platform height 0.2 m	Platform height 0.4 m	Platform height 0.6 m
Transport dimensions 600 mm × 406 mm × 200 mm	Transport dimensions 671 mm × 639 mm × 400 mm	Transport dimensions 692 mm × 871 mm × 600 mm
Weight 3 kg	Weight 5.5 kg	Weight 7.8 kg
Working height 2.2 m	Working height 2.4 m	Working height 2.6 m
SKU 40034	SKU 40035	
Base 1,1 m × 0,71 m	Base 1,35 m × 0,73 m	



Number of rungs, incl. platform 4	Number of rungs, incl. platform 5
Platform height 0.8 m	Platform height 0.99 m
Transport dimensions 713 mm × 1.103 mm × 800 mm	Transport dimensions 734 mm × 1.336 mm × 1.000 mm
Weight 10.1 kg	Weight 13.5 kg
Working height 2.8 m	Working height 3 m