



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.

Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7

Product features





| | |
|--|----------------------------|
| Coating | natural |
| Connection between stiles and rungs/stiles | welded |
| Guardrail height | 1000 mm |
| Load capacity | max. 150 kg |
| Material | Aluminum/steel, galvanised |
| Platform length | 800 mm |
| Platform width | 600 mm |
| Standards | EN 131-7 |
| Tread depth | 200 mm |
| Type of rungs/treads | Open-grid surface |
| Vertical distance between each rung/tread | 240 mm |
| Warranty | 10 years |

Product variants

| | 41951 | 41952 | 41953 | 41954 | 41955 | 41956 |
|---------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|------------------------------|
| Base | 0,77 m × 1,27 m | 0,82 m × 1,45 m | 0,87 m × 1,63 m | 0,93 m × 1,81 m | 0,98 m × 1,99 m | 1,03 m × 2,17 m |
| Number of rungs, incl. platform | 3 | 4 | 5 | 6 | 7 | 8 |
| Platform height | 0.72 m | 0.96 m | 1.2 m | 1.44 m | 1.68 m | 1.92 m |
| Transport dimensions | 1.150 mm × 780 mm × 350 mm | 1.350 mm × 830 mm × 410 mm | 1.500 mm × 890 mm × 410 mm | 1.820 mm × 930 mm × 350 mm | 1.920 mm × 990 mm × 350 mm | 2.220 mm × 1.130 mm × 350 mm |
| Weight | 41.5 kg | 47.5 kg | 53.6 kg | 59.7 kg | 66 kg | 72.9 kg |
| Working height | 2.7 m | 2.95 m | 3.2 m | 3.45 m | 3.7 m | 3.9 m |



More information about the product, accessories and spare parts:
<https://www.zarges.com/uk/products/mobile-access-steps-with-platform-single-sided-access-with-steel-open-grid-treads-and-platform>



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 4/6/2026
Subject to change or error.