



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.



Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.

Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7

Product features



Coating natural	Connection between stiles and rungs/stiles welded	Guardrail height 1000 mm	Load capacity max. 150 kg	Material Aluminum/steel, galvanised
Platform length 800 mm	Platform width 600 mm	Standards EN 131-7	Tread depth 200 mm	Type of rungs/treads Open-grid surface
Vertical distance between each rung/ tread 240 mm	Warranty 10 years			

Product variants

SKU 41951	SKU 41952	SKU 41953
Base 0,77 m × 1,27 m	Base 0,82 m × 1,45 m	Base 0,87 m × 1,63 m
Number of rungs, incl. platform 3	Number of rungs, incl. platform 4	Number of rungs, incl. platform 5
Platform height 0.72 m	Platform height 0.96 m	Platform height 1.2 m
Transport dimensions 1.150 mm × 780 mm × 350 mm	Transport dimensions 1.350 mm × 830 mm × 410 mm	Transport dimensions 1.500 mm × 890 mm × 410 mm
Weight 41.5 kg	Weight 47.5 kg	Weight 53.6 kg
Working height 2.7 m	Working height 2.95 m	Working height 3.2 m
SKU	SKU	SKU



41954	41955	41956
Base	Base	Base
0,93 m × 1,81 m	0,98 m × 1,99 m	1,03 m × 2,17 m
Number of rungs, incl. platform	Number of rungs, incl. platform	Number of rungs, incl. platform
6	7	8
Platform height	Platform height	Platform height
1.44 m	1.68 m	1.92 m
Transport dimensions	Transport dimensions	Transport dimensions
1.820 mm × 930 mm × 350 mm	1.920 mm × 990 mm × 350 mm	2.220 mm × 1.130 mm × 350 mm
Weight	Weight	Weight
59.7 kg	66 kg	72.9 kg
Working height	Working height	Working height
3.45 m	3.7 m	3.9 m