



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

| | | | | |
|-----------------------------------|--|------------------------------------|-------------------------------------|---|
| Coating natural | Connection Stile-Rung welded | Guardrail height 1000 mm | Load capacity max. 150 kg | Material Aluminum/steel, galvanised |
| Pitch rung/tread 240 mm | Platform length 800 mm | Platform width 600 mm | Standards EN 131-7 | Tread depth 200 mm |



| | |
|--------------------------|-----------------|
| Type rung/tread | Warranty |
| Open-grid surface | 10 years |

Product variants

| | | |
|---|---|---|
| SKU 41951 | SKU 41952 | SKU 41953 |
| Base 0,77 m × 1,27 m | Base 0,82 m × 1,45 m | Base 0,87 m × 1,63 m |
| Number of rungs, incl. platform 3 | Number of rungs, incl. platform 4 | Number of rungs, incl. platform 5 |
| Platform height 0.72 m | Platform height 0.96 m | Platform height 1.2 m |
| Transport dimensions 1.150 mm × 780 mm × 350 mm | Transport dimensions 1.350 mm × 830 mm × 410 mm | Transport dimensions 1.500 mm × 890 mm × 410 mm |
| Weight 41.5 kg | Weight 47.5 kg | Weight 53.6 kg |
| Working height 2.7 m | Working height 2.95 m | Working height 3.2 m |
| SKU 41954 | SKU 41955 | SKU 41956 |
| Base 0,93 m × 1,81 m | Base 0,98 m × 1,99 m | Base 1,03 m × 2,17 m |
| Number of rungs, incl. platform 6 | Number of rungs, incl. platform 7 | Number of rungs, incl. platform 8 |
| Platform height 1.44 m | Platform height 1.68 m | Platform height 1.92 m |



| | | |
|---|---|---|
| Transport dimensions 1.820 mm × 930 mm × 350 mm | Transport dimensions 1.920 mm × 990 mm × 350 mm | Transport dimensions 2.220 mm × 1.130 mm × 350 mm |
| Weight 59.7 kg | Weight 66 kg | Weight 72.9 kg |
| Working height 3.45 m | Working height 3.7 m | Working height 3.9 m |