



# Mobile access steps with platform, double-sided access, with light-alloy treads and platform

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.

## Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



## Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>welded</b>	Guardrail height <b>1000 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Pitch rung/tread <b>240 mm</b>	Platform length <b>800 mm</b>	Platform width <b>600 mm</b>	Standards <b>EN 131-7</b>	Tread depth <b>200 mm</b>



Type rung/tread  
**serrated**

Warranty  
**10 years**

## Product variants

SKU <b>41981</b>	SKU <b>41982</b>	SKU <b>41983</b>
Base <b>0,77 m × 1,51 m</b>	Base <b>0,82 m × 1,79 m</b>	Base <b>0,87 m × 2,06 m</b>
Number of rungs, incl. platform <b>2 × 3</b>	Number of rungs, incl. platform <b>2 × 4</b>	Number of rungs, incl. platform <b>2 × 5</b>
Number of treads <b>3</b>	Number of treads <b>4</b>	Number of treads <b>5</b>
Platform height <b>0.72 m</b>	Platform height <b>0.96 m</b>	Platform height <b>1.2 m</b>
Transport dimensions <b>1.300 mm × 820 mm × 470 mm</b>	Transport dimensions <b>1.980 mm × 880 mm × 300 mm</b>	Transport dimensions <b>1.850 mm × 940 mm × 440 mm</b>
Weight <b>31.2 kg</b>	Weight <b>36 kg</b>	Weight <b>41 kg</b>
Working height <b>2.7 m</b>	Working height <b>2.95 m</b>	Working height <b>3.2 m</b>
SKU <b>41984</b>	SKU <b>41985</b>	SKU <b>41986</b>
Base <b>0,93 m × 2,34 m</b>	Base <b>0,98 m × 2,62 m</b>	Base <b>1,03 m × 2,9 m</b>
Number of rungs, incl. platform <b>2 × 6</b>	Number of rungs, incl. platform <b>2 × 7</b>	Number of rungs, incl. platform <b>2 × 8</b>
Number of treads	Number of treads	Number of treads



6	7	8
Platform height <b>1.44 m</b>	Platform height <b>1.68 m</b>	Platform height <b>1.92 m</b>
Transport dimensions <b>2.200 mm × 1.020 mm × 410 mm</b>	Transport dimensions <b>2.250 mm × 1.060 mm × 410 mm</b>	Transport dimensions <b>2.820 mm × 1.120 mm × 410 mm</b>
Weight <b>46.2 kg</b>	Weight <b>51.7 kg</b>	Weight <b>57.5 kg</b>
Working height <b>3.45 m</b>	Working height <b>3.7 m</b>	Working height <b>3.9 m</b>