



Mobile access steps with platform, double-sided access, with aluminium treads and platform

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.



Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through double-sided platform guardrail at a height of 1.00 m.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.



Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



Product features

Coating natural	Connection between stiles and rungs/stiles welded	Guardrail height 1000 mm	Load capacity max. 150 kg	Material aluminium
Platform length 800 mm	Platform width 600 mm	Standards EN 131-7	Tread depth 200 mm	Type of rungs/treads serrated
Vertical distance between each rung/tread 240 mm	Warranty 10 years			

Product variants

SKU 41981	SKU 41982	SKU 41983
Base 0,77 m × 1,51 m	Base 0,82 m × 1,79 m	Base 0,87 m × 2,06 m
Number of rungs, incl. platform 2 × 3	Number of rungs, incl. platform 2 × 4	Number of rungs, incl. platform 2 × 5
Number of treads 3	Number of treads 4	Number of treads 5
Platform height 0.72 m	Platform height 0.96 m	Platform height 1.2 m
Transport dimensions 1.300 mm × 820 mm × 470 mm	Transport dimensions 1.980 mm × 880 mm × 300 mm	Transport dimensions 1.850 mm × 940 mm × 440 mm
Weight 31.2 kg	Weight 36 kg	Weight 41 kg



Working height 2.7 m	Working height 2.95 m	Working height 3.2 m
SKU 41984	SKU 41985	SKU 41986
Base 0,93 m × 2,34 m	Base 0,98 m × 2,62 m	Base 1,03 m × 2,9 m
Number of rungs, incl. platform 2 × 6	Number of rungs, incl. platform 2 × 7	Number of rungs, incl. platform 2 × 8
Number of treads 6	Number of treads 7	Number of treads 8
Platform height 1.44 m	Platform height 1.68 m	Platform height 1.92 m
Transport dimensions 2.200 mm × 1.020 mm × 410 mm	Transport dimensions 2.250 mm × 1.060 mm × 410 mm	Transport dimensions 2.820 mm × 1.120 mm × 410 mm
Weight 46.2 kg	Weight 51.7 kg	Weight 57.5 kg
Working height 3.45 m	Working height 3.7 m	Working height 3.9 m