



Mobile access steps with platform, double-sided access, with steel open-grid treads and platform

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.

Product description

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

Coating natural	Connection Stile-Rung welded	Guardrail height 1000 mm	Load capacity max. 150 kg	Material Aluminum/steel, galvanised
Pitch rung/tread 240 mm	Platform length 800 mm	Platform width 600 mm	Standards EN 131-7	Tread depth 200 mm
Type rung/tread	Warranty			



**Open-grid
surface**

10 years

Product variants

SKU 41962	SKU 41963	SKU 41964
Base 0,82 m × 1,79 m	Base 0,87 m × 2,06 m	Base 0,93 m × 2,34 m
Number of rungs, incl. platform 2 × 4	Number of rungs, incl. platform 2 × 5	Number of rungs, incl. platform 2 × 6
Number of treads 4	Number of treads 5	Number of treads 6
Platform height 0.96 m	Platform height 1.2 m	Platform height 1.44 m
Transport dimensions 1.960 mm × 830 mm × 300 mm	Transport dimensions 1.850 mm × 890 mm × 460 mm	Transport dimensions 2.140 mm × 930 mm × 380 mm
Weight 59.2 kg	Weight 70.1 kg	Weight 80.7 kg
Working height 2.95 m	Working height 3.2 m	Working height 3.45 m