



ZAP Telemaster S

Secure and flexible: height adjustable platform with all-round railing for stability, easy to adjust with compact closed dimensions.

Product description

- Height-adjustable platform with large standing surface and all-round railings for safe and comfortable footing.
- Simple height adjustment according to the push-up ladder principle, thus different heights can be obtained with only one platform ladder.
- Very easy to erect - handrails and guardrails unfold automatically during erection.
- Can be used on stairs and folded to a very compact size for transport and storage.
- The two rear wheels make it easy to move.
- Large standing surface, 665 × 440 mm, made of 7-ply adhesive-bonded plywood board, with guardrail and knee bar, ensures maximum work safety and comfortable standing.
- Complies with new European standard DIN EN 131-7.
- Can be easily moved even when fully set up thanks to pair of wheels.
- Compact dimensions when folded, therefore easy to transport and store.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Can be used on steps/stairs.





- Order No. 41325 without stabiliser.
- Required number of ballast weights when used outdoors: 4x (order no. 41331).

Product features

Guardrail height 1 m	Length 0.4 m	Load capacity max. 150 kg	Platform length 665 mm	Platform material 7-layer laminated plywood
Platform width 440 mm	Standards EN 131-7	Storage tray aluminium	Tread depth 30 mm	Warranty 10 years

Product variants

SKU 41325	SKU 41326	SKU 41327
Footpoint, stabiliser rod extended L x W 1,45m × 1 m	Footpoint, stabiliser rod extended L x W 1,8m × 2,25 m	Footpoint, stabiliser rod extended L x W 2,2m × 2,55 m
Footpoint, stabiliser rod retracted L x W 1,45m × 1 m	Footpoint, stabiliser rod retracted L x W 1,8m × 0,81 m	Footpoint, stabiliser rod retracted L x W 2,2m × 0,81 m
Height including railing max. 2.37 m	Height including railing max. 2.86 m	Height including railing max. 3.38 m
No. of rungs incl. platform 5	No. of rungs incl. platform 7	No. of rungs incl. platform 9
Platform height 0,81m / 1,08m / 1,34m	Platform height 1,05m / 1,3m / 1,6m / 1,83m	Platform height 1,31m / 1,6m / 1,8m / 2,1m / 2,35m



Transport dimensions	Transport dimensions	Transport dimensions
2.160 mm × 1.020 mm × 400 mm	2.440 mm × 820 mm × 400 mm	2.720 mm × 820 mm × 400 mm
Weight	Weight	Weight
28 kg	34 kg	38.5 kg
Width	Width	Width
2.16 m	2.44 m	2.72 m
Width, extended	Width, extended	Width, extended
1 m	2.25 m	2.55 m
Width, retracted	Width, retracted	Width, retracted
1 m	0.81 m	0.81 m
Working height	Working height	Working height
3.34 m	3.83 m	4.35 m
closed length	closed length	closed length
1.45 m	1.8 m	2.2 m
extended length	extended length	extended length
1.45 m	1.8 m	2.2 m
SKU		
41328		
Footpoint, stabiliser rod extended L x W		
2,8m × 2,5 m		
Footpoint, stabiliser rod retracted L x W		
2,8m × 0,81 m		
Height including railing		
max. 4.17 m		
No. of rungs incl. platform		



12

Platform height

**1,83m / 2,12m / 2,38m / 2,65m /
2,9m / 3,15m**

Transport dimensions

3.280 mm × 820 mm × 400 mm

Weight

50 kg

Width

3.28 m

Width, extended

2.5 m

Width, retracted

0.81 m

Working height

5.15 m

closed length

2.8 m

extended length

2.8 m