





Single-section fixed ladder systems up to a height of 10 m, anodised aluminium

Stationary access to buildings and machinery up to a height of 10 m, also suitable and approved for use as an escape route.

Product description

- For stationary mounting, on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- Safety cage as safety system, complies with any standard.
- Arrester rail as a safety system in accordance with DIN EN 353-1, DIN 18 799-1 and DIN EN ISO 14 122-4, can be supplied as a single-section fixed ladder even with climbing heights of over 10 m.
- Ladder width: 520 mm.
- Wall brackets with various wall clearances of up to 600 mm can be selected.
- The maximum permissible distance between two wall brackets is 2.00 m. But each ladder section must be mounted with at least two wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- We can also produce fixed-ladder designs that differ from the standard specification on request.





Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.

The prices for single-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, incl. back cage in accordance with DIN 18799-1. In the case of other requirements, please use our planning system for fixed ladders.

Product features

Material	Anodised aluminium
Warranty	10 years

Product variants

	58148	58157	58165	58174	58185	58196
Overall length incl. stile	5.9 m	6.7 m	7.6 m	8.5 m	9.6 m	10.7 m
access height	4.8 m	5.6 m	6.5 m	7.4 m	8.5 m	9.6 m

ZARGES (U.K.) Ltd. 8 Holdom Avenue, Saxon Park Ind. Est. Bletchley MK1 1QU	Tel: 01908 641118	www.zarges.com/uk
	Fax:	Effective 13/5/2026
	sales@zarges.co.uk	Subject to change or error.