



# Multi-section fixed ladder systems, anodised aluminium

Multi-section access solution with crossover platform for buildings and machinery.

## Product description

- For permanent mounting on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- With safety cage.
- Ladder width: 520 mm.
- Wall brackets with various wall clearances of up to 600 mm can be selected.
- The maximum permissible distance between two wall brackets is 2.00 m. But each ladder section must be mounted with at least two wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- We can also produce fixed-ladder designs that differ from the standard specification on request.



## Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.

The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both



sides, crossover platform, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for fixed ladders.

## Product features

Material	Anodised aluminium
Warranty	10 years

## Product variants

	58507	58518	58526	58538	58549	58557
Overall length incl. stile	11.8 m	12.9 m	13.7 m	14.9 m	16 m	16.8 m
access height	10.7 m	11.8 m	12.6 m	13.8 m	14.9 m	15.7 m

  

	58568	58580	58591
Overall length incl. stile	17.9 m	19.1 m	20.2 m
access height	16.8 m	18 m	19.1 m

<b>ZARGES (U.K.) Ltd.</b> Blackwater Trading Estate, The Causeway CM9 4LJ Maldon, Essex	Tel: 01908 641118	<a href="http://www.zarges.com/uk">www.zarges.com/uk</a>
	Fax:	Effective 27/6/2026
	<a href="mailto:sales@zarges.co.uk">sales@zarges.co.uk</a>	Subject to change or error.