
DATA SHEET

Multi-section fixed ladder systems, natural alumini

Multi-section access solution with crossover platform for buildings and machinery.







PRODUCT DESCRIPTION

- For permanent mounting on buildings either for maintenance in accordance with DIN 18 799-1 or as an emergency ladder system in accordance with DIN 14 094-1 or as machine access steps in accordance with DIN EN ISO 14 122-4.
- With safety cage.
- Ladder width: 520 mm.
- Wall brackets with various wall clearances of up to 600 mm can be selected.
- The maximum permissible distance between two wall brackets is 2.00 m. But each ladder section must be mounted with at least two wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- We can also produce fixed-ladder designs that differ from the standard specification on request.

HINTS AND SPECIAL FEATURES

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.
The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, crossover platform, incl. back cage in accordance with DIN 18 799-1.In the case of other requirements, please use our planning system for fixed ladders.

PRODUCT FEATURES

Property	Value
Material	Natural aluminium

Property	Value
Warranty	10 years

PRODUCT VARIANTS

	58607	58618	58626	58638	58649	58657
Overall length incl. stile	11.8 m	12.9 m	13.7 m	14.9 m	16 m	16.8 m
access height	10.7 m	11.8 m	12.6 m	13.8 m	14.9 m	15.7 m

	58668	58680	58691
Overall length incl. stile	17.9 m	19.1 m	20.2 m
access height	16.8 m	18 m	19.1 m

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 10/11/2026
Subject to change or error.