



# Well covers, round

## Product description

- Lid made from sheet metal, 2.5 mm thick, elevated in the centre, with internal transverse bracing
- From 800 x 800 mm or  $\varnothing$  800 mm with gas pressure spring.
- Self-closing fastener, hold-open device can only be released by hand.
- Frame prepared for setting in concrete and attachment with dowels.



## Product features

|       |                                     |
|-------|-------------------------------------|
| Shape | Round without a ventilation chimney |
|-------|-------------------------------------|

## Product variants

|                                   | 47156                    | 47157                    | 47158                        | 47162                    | 47163                    | 47164                        |
|-----------------------------------|--------------------------|--------------------------|------------------------------|--------------------------|--------------------------|------------------------------|
| Inside shaft size                 | 625 mm                   | 800 mm                   | 1000 mm                      | 625 mm                   | 800 mm                   | 1000 mm                      |
| Material                          | Steel, galvanised        | Steel, galvanised        | Steel, galvanised            | Steel, galvanised        | Galvanised steel         | Steel, galvanised            |
| Outside dimensions max. L x W x H | 745 mm                   | 920 mm                   | 1120 mm                      | 745 mm                   | 920 mm                   | 1120 mm                      |
| Transport dimensions              | 740 mm x 740 mm x 200 mm | 920 mm x 920 mm x 200 mm | 1.120 mm x 1.120 mm x 200 mm | 740 mm x 740 mm x 200 mm | 920 mm x 920 mm x 200 mm | 1.120 mm x 1.120 mm x 200 mm |
| Version                           | without insulation       | without insulation       | without insulation           | with insulation          | with insulation          | with insulation              |



|                                   | 47159                    | 47160                    | 47161                        | 47165                    | 47166                    | 47167                        |
|-----------------------------------|--------------------------|--------------------------|------------------------------|--------------------------|--------------------------|------------------------------|
| Inside shaft size                 | 625 mm                   | 800 mm                   | 1000 mm                      | 625 mm                   | 800 mm                   | 1000 mm                      |
| Material                          | stainless steel          | stainless steel          | stainless steel              | –                        | –                        | –                            |
| Outside dimensions max. L x W x H | 745 mm                   | 920 mm                   | 1120 mm                      | 745 mm                   | 920 mm                   | 1120 mm                      |
| Transport dimensions              | 740 mm x 740 mm x 200 mm | 920 mm x 920 mm x 200 mm | 1.120 mm x 1.120 mm x 200 mm | 740 mm x 740 mm x 200 mm | 920 mm x 920 mm x 200 mm | 1.120 mm x 1.120 mm x 200 mm |
| Version                           | without insulation       | without insulation       | without insulation           | with insulation          | with insulation          | with insulation              |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 27/6/2026  
 Subject to change or error.