




Steel shaft covers, galvanised steel with trough

Walkable or drivable shaft covers with choice of surface for indoor and outdoor use.

Product description

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapered profile-section construction with multiple bolted joints.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load capacity for shaft cover with cover trough: test force 125 kN (= 12.5 t), only after the cover trough has been filled with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 80 mm (of which 40 mm covered with construction steel grating and 40 mm free area)



Product features

Design height	90 mm
Material, cover	Steel, galvanised
Material, frame	Steel, galvanised
Trough depth	80 mm



Product variants

	47030	47031	47032	47033	47034	47035
Inside shaft length	450 mm	500 mm	600 mm	600 mm	635 mm	800 mm
Inside shaft size	450mm x 450mm	500mm x 500mm	600mm x 400mm	600mm x 600mm	635mm x 635mm	800mm x 600mm
Inside shaft width	450 mm	500 mm	400 mm	600 mm	635 mm	600 mm
Outside dimensions max. L x W x H	570 mm x 570 mm	620 mm x 620 mm	720 mm x 520 mm	720 mm x 720 mm	755 mm x 755 mm	920 mm x 720 mm
Transport dimensions	570 mm x 570 mm x 70 mm	620 mm x 620 mm x 70 mm	720 mm x 520 mm x 70 mm	720 mm x 720 mm x 70 mm	750 mm x 770 mm x 90 mm	920 mm x 720 mm x 90 mm

	47036	47037	47038	47039
Inside shaft length	800 mm	1000 mm	1000 mm	1000 mm
Inside shaft size	800mm x 800mm	1.000mm x 600mm	1.000mm x 800mm	1.000mm x 1.000mm
Inside shaft width	800 mm	600 mm	800 mm	1000 mm
Outside dimensions max. L x W x H	920 mm x 920 mm	1.120 mm x 720 mm	1.120 mm x 920 mm	1.120 mm x 1.120 mm
Transport dimensions	920 mm x 920 mm x 90 mm	1.120 mm x 720 mm x 90 mm	1.120 mm x 920 mm x 90 mm	1.120 mm x 1.120 mm x 90 mm

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
 sales@zarges.co.uk

www.zarges.com/uk

Effective 29/6/2026
 Subject to change or error.