


DATA SHEET

Stainless steel shaft covers with trough


Walkable or drivable shaft covers with choice of surface for indoor and outdoor use.











PRODUCT DESCRIPTION

- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapered profile-section construction with multiple bolted joints.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load capacity for shaft cover with cover trough: test force 125 kN (= 12.5 t), only after the cover trough has been filled with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 80 mm (of which 40 mm covered with construction steel grating and 40 mm free area)

PRODUCT FEATURES

Property	Value
Design height	90 mm
Trough depth	80 mm

PRODUCT VARIANTS

	47060	47061	47062	47064	47065	47067
Inside shaft length	300 mm	450 mm	500 mm	600 mm	635 mm	800 mm
Inside shaft size	300mm × 300mm	450mm × 450mm	500mm × 500mm	600mm × 600mm	635mm × 635mm	800mm × 800mm
Inside shaft width	300 mm	450 mm	500 mm	600 mm	635 mm	800 mm
Outside dimensions max. L x W x H	420 mm × 420 mm	570 mm × 570 mm	620 mm × 620 mm	720 mm × 720 mm	755 mm × 755 mm	920 mm × 920 mm
Transport dimensions	420 mm × 420 mm × 90 mm	570 mm × 570 mm × 90 mm	620 mm × 620 mm × 90 mm	720 mm × 720 mm × 90 mm	750 mm × 750 mm × 90 mm	920 mm × 920 mm × 90 mm

	47070
Inside shaft length	1000 mm
Inside shaft size	1.000mm × 1.000mm
Inside shaft width	1000 mm
Outside dimensions max. L x W x H	1.120 mm × 1.120 mm
Transport dimensions	1.120 mm × 1.120 mm × 90 mm

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 13/11/2026
Subject to change or error.