DATA SHEET

Mobile platform steps with ZARGES Ergo Stop

Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.





PRODUCT DESCRIPTION

- Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- An antistatic version of the chassis is also available.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the foot pedal on the flight of steps.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

HINTS AND SPECIAL FEATURES

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.
Standard applied: DIN EN ISO 14 122.

PRODUCT FEATURES

Property	Value
Load capacity	max. 300 kg
Max. load per tread	150 kg
Platform length	600 mm
Standards	NF EN ISO 14122-4
Warranty	10 years

PRODUCT VARIANTS

	40255014	40255016	40255018	40255020	40255022	40255024
Chassis width	1020 mm	1620 mm	1620 mm	1220 mm	1220 mm	1220 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	5	7	9	11	12	14
Overall span	1698 mm	2128 mm	2558 mm	3017 mm	3447 mm	3877 mm
Tread width	600 mm	600 mm	600 mm	600 mm	600 mm	600 mm
Vertical height	1070 mm	1500 mm	1930 mm	2360 mm	2790 mm	3220 mm

	40255026	40255028	40255030	40255034	40255036	40255038
Chassis width	1220 mm	1420 mm	1420 mm	1020 mm	1220 mm	1220 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	16	18	20	5	7	9
Overall span	4307 mm	4737 mm	5167 mm	1698 mm	2128 mm	2558 mm
Tread width	600 mm	600 mm	600 mm	800 mm	800 mm	800 mm
Vertical height	3650 mm	4080 mm	4510 mm	1070 mm	1500 mm	1930 mm

	40255040	40255042	40255044	40255046	40255048	40255050
Chassis width	1220 mm	1220 mm	1420 mm	1420 mm	1420 mm	1620 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	11	12	14	16	18	20
Overall span	3017 mm	3447 mm	3877 mm	4307 mm	4737 mm	5167 mm
Tread width	800 mm	800 mm	800 mm	800 mm	800 mm	800 mm
Vertical height	2360 mm	2790 mm	3220 mm	3650 mm	4080 mm	4510 mm

	40255054	40255056	40255058	40255060	40255062	40255064
Chassis width	1420 mm	1420 mm	1420 mm	1420 mm	1420 mm	1420 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	5	7	9	11	12	14
Overall span	1698 mm	2128 mm	2558 mm	3017 mm	3447 mm	3877 mm
Tread width	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm
Vertical height	1070 mm	1500 mm	1930 mm	2360 mm	2790 mm	3220 mm

	40255066	40255068	40255070	40255074	40255076	40255078
Chassis width	1420 mm	1420 mm	1620 mm	1220 mm	1420 mm	1820 mm
Inclination	45 °	45 °	45 °	60 °	60 °	60 °
Number of treads	16	18	20	5	7	9
Overall span	4307 mm	4737 mm	5167 mm	1453 mm	1707 mm	1996 mm
Tread width	1000 mm	1000 mm	1000 mm	600 mm	600 mm	600 mm
Vertical height	3650 mm	4080 mm	4510 mm	1250 mm	1750 mm	2250 mm

	40255080	40255082	40255084	40255086	40255094	40255096
Chassis width	1620 mm	1620 mm	1620 mm	1620 mm	1220 mm	1220 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	11	13	15	17	5	7
Overall span	2285 mm	2607 mm	2896 mm	3185 mm	1453 mm	1707 mm
Tread width	600 mm	600 mm	600 mm	600 mm	800 mm	800 mm
Vertical height	2750 mm	3250 mm	3750 mm	4250 mm	1250 mm	1750 mm

	40255098	40255100	40255102	40255104	40255106	40255114
Chassis width	1620 mm	1420 mm	1420 mm	1420 mm	1620 mm	1420 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	9	11	12	15	17	5
Overall span	1996 mm	2285 mm	2607 mm	2896 mm	3185 mm	1453 mm
Tread width	800 mm	800 mm	800 mm	800 mm	800 mm	1000 mm
Vertical height	2250 mm	2750 mm	3250 mm	3750 mm	4250 mm	1250 mm

	40255116	40255118	40255120	40255122	40255124	40255126
Chassis width	1420 mm	1420 mm	1420 mm	1420 mm	1620 mm	1620 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	7	9	11	13	14	17
Overall span	1707 mm	1820 mm	2285 mm	2607 mm	3009 mm	3298 mm
Tread width	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm
Vertical height	1750 mm	2250 mm	2750 mm	3250 mm	3750 mm	4250 mm

ACCESSORIES AND SPARE PARTS

ACCESSORIES 3



impact protection
SKU 41250 · 41252 · 41254



Storage and retrieval tray
SKU 41968



Storage tray
SKU 41967

SPARE PARTS 1

clamping lever
SKU 800512 · 42355279 · 42355276

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 7/11/2026
Subject to change or error.