



## Platform steps

Compact work platform with easy-going steps. Choice of stationary or mobile version (for moving quickly to another working position). Ideal for work over long periods, even with tools.

### Product description

- Compact work platform with easy access. Ideal for extended work sessions, even when using tools.



### Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.



### Product features

|                     |             |
|---------------------|-------------|
| Load capacity       | max. 300 kg |
| Max. load per tread | 150 kg      |
| Platform length     | 400 mm      |
| Warranty            | 10 years    |

### Product variants



|                  | 40855520 | 40855521 | 40855522 | 40855523 | 40855524 | 40855525 |
|------------------|----------|----------|----------|----------|----------|----------|
| Inclination      | 45 °     | 45 °     | 45 °     | 45 °     | 45 °     | 45 °     |
| Number of treads | 2        | 3        | 4        | 5        | 2        | 3        |
| Overall span     | 951 mm   | 1151 mm  | 1351 mm  | 1541 mm  | 951 mm   | 1151 mm  |
| Tread width      | 600 mm   | 600 mm   | 600 mm   | 600 mm   | 800 mm   | 800 mm   |
| Vertical height  | 400 mm   | 600 mm   | 800 mm   | 990 mm   | 400 mm   | 600 mm   |

|                  | 40855526 | 40855527 | 40855528 | 40855529 | 40855530 | 40855531 |
|------------------|----------|----------|----------|----------|----------|----------|
| Inclination      | 45 °     | 45 °     | 45 °     | 45 °     | 45 °     | 45 °     |
| Number of treads | 4        | 5        | 2        | 3        | 4        | 5        |
| Overall span     | 1351 mm  | 1541 mm  | 951 mm   | 1151 mm  | 1351 mm  | 1541 mm  |
| Tread width      | 800 mm   | 800 mm   | 1000 mm  | 1000 mm  | 1000 mm  | 1000 mm  |
| Vertical height  | 800 mm   | 990 mm   | 400 mm   | 600 mm   | 800 mm   | 990 mm   |

|                  | 40855540 | 40855541 | 40855542 | 40855544 | 40855545 | 40855546 |
|------------------|----------|----------|----------|----------|----------|----------|
| Inclination      | 60 °     | 60 °     | 60 °     | 60 °     | 60 °     | 60 °     |
| Number of treads | 2        | 3        | 4        | 2        | 3        | 4        |
| Overall span     | 864 mm   | 1008 mm  | 1147 mm  | 864 mm   | 1008 mm  | 1147 mm  |
| Tread width      | 600 mm   | 600 mm   | 600 mm   | 800 mm   | 800 mm   | 800 mm   |
| Vertical height  | 500 mm   | 750 mm   | 990 mm   | 500 mm   | 750 mm   | 990 mm   |

|                  | 40855548 | 40855549 | 40855550 |
|------------------|----------|----------|----------|
| Inclination      | 60 °     | 60 °     | 60 °     |
| Number of treads | 2        | 3        | 4        |
| Overall span     | 864 mm   | 1008 mm  | 1147 mm  |
| Tread width      | 1000 mm  | 1000 mm  | 1000 mm  |
| Vertical height  | 500 mm   | 750 mm   | 990 mm   |



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 20/5/2026  
Subject to change or error.