



## Stationary bridging steps

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.

### Product description

- Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.



### Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with



platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

## Product features

Load capacity	max. 300 kg
Max. load per tread	150 kg
Platform length	600 mm
Standards	NF EN ISO 14122-4
Warranty	10 years

## Product variants

	40355933	40355934	40355935	40355936	40355937	40355938
Clear height, stationary	740 mm	950 mm	1170 mm	1380 mm	1600 mm	1810 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	4	5	6	7	8	9
Overall span	2431 mm	2851 mm	3291 mm	3711 mm	4151 mm	4571 mm
Tread width	600 mm					

	40355939	40355940	40355943	40355944	40355945	40355946
Clear height, stationary	2030 mm	2240 mm	740 mm	950 mm	1170 mm	1380 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	10	11	4	5	6	7
Overall span	5011 mm	5431 mm	2431 mm	2851 mm	3291 mm	3711 mm
Tread width	600 mm	600 mm	800 mm	800 mm	800 mm	800 mm



	40355947	40355948	40355949	40355950	40355953	40355954
Clear height, stationary	1600 mm	1810 mm	2030 mm	2240 mm	740 mm	950 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	8	9	10	11	4	5
Overall span	4151 mm	4571 mm	5011 mm	5431 mm	2431 mm	2851 mm
Tread width	800 mm	800 mm	800 mm	800 mm	1000 mm	1000 mm

	40355955	40355956	40355957	40355958	40355959	40355960
Clear height, stationary	1170 mm	1380 mm	1600 mm	1810 mm	2030 mm	2240 mm
Inclination	45 °	45 °	45 °	45 °	45 °	45 °
Number of treads	6	7	8	9	10	11
Overall span	3291 mm	3711 mm	4151 mm	4571 mm	5011 mm	5431 mm
Tread width	1000 mm					

	40355903	40355904	40355905	40355906	40355907	40355908
Clear height, stationary	880 mm	1130 mm	1380 mm	1630 mm	1880 mm	2130 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	4	5	6	7	8	9
Overall span	1915 mm	2203 mm	2492 mm	2781 mm	3069 mm	3358 mm
Tread width	600 mm					

	40355909	40355910	40355913	40355914	40355915	40355916
Clear height, stationary	2380 mm	2630 mm	880 mm	1130 mm	1380 mm	1630 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	10	11	4	5	6	7
Overall span	3647 mm	3935 mm	1915 mm	2203 mm	2492 mm	2781 mm
Tread width	600 mm	600 mm	800 mm	800 mm	800 mm	800 mm



	40355917	40355918	40355919	40355920	40355923	40355924
Clear height, stationary	1880 mm	2130 mm	2380 mm	2630 mm	880 mm	1130 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	8	9	10	11	4	5
Overall span	3069 mm	3358 mm	3647 mm	3935 mm	1915 mm	2203 mm
Tread width	800 mm	800 mm	800 mm	800 mm	1000 mm	1000 mm

	40355925	40355926	40355927	40355928	40355929	40355930
Clear height, stationary	1380 mm	1630 mm	1880 mm	2130 mm	2380 mm	2630 mm
Inclination	60 °	60 °	60 °	60 °	60 °	60 °
Number of treads	6	7	8	9	10	11
Overall span	2492 mm	2781 mm	3069 mm	3358 mm	3647 mm	3935 mm
Tread width	1000 mm					

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 22/5/2026  
 Subject to change or error.