

Stationary bridging steps

Stationary or mobile platform for bridging obstacles
 or as a work platform with access from both sides.
 Large-area platform with guardrail for safe and
 ergonomic working at heights.

Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.



Hints and special features

We recommend equipping the product in accordance
 with the German Equipment and Product Safety Act
 (ProdSG) with two-sided handrails and, for steps with



platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.


Standard applied: DIN EN ISO 14 122.

Product features

Load capacity	Max. load per tread	Platform length	Standards	Warranty
max. 300 kg	150 kg	600 mm	NF EN ISO 14122-4	10 years

Product variants


SKU 40355933	SKU 40355934	SKU 40355935
Clear height, stationary 740 mm	Clear height, stationary 950 mm	Clear height, stationary 1170 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 4	Number of treads 5	Number of treads 6
Overall span 2431 mm	Overall span 2851 mm	Overall span 3291 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
SKU 40355936	SKU 40355937	SKU 40355938



Clear height, stationary 1380 mm	Clear height, stationary 1600 mm	Clear height, stationary 1810 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 7	Number of treads 8	Number of treads 9
Overall span 3711 mm	Overall span 4151 mm	Overall span 4571 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
SKU 40355939	SKU 40355940	SKU 40355943
Clear height, stationary 2030 mm	Clear height, stationary 2240 mm	Clear height, stationary 740 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 10	Number of treads 11	Number of treads 4
Overall span 5011 mm	Overall span 5431 mm	Overall span 2431 mm
Tread width 600 mm	Tread width 600 mm	Tread width 800 mm
SKU 40355944	SKU 40355945	SKU 40355946
Clear height, stationary	Clear height, stationary	Clear height, stationary




950 mm	1170 mm	1380 mm
Inclination	Inclination	Inclination
45 °	45 °	45 °
Number of treads	Number of treads	Number of treads
5	6	7
Overall span	Overall span	Overall span
2851 mm	3291 mm	3711 mm
Tread width	Tread width	Tread width
800 mm	800 mm	800 mm
SKU	SKU	SKU
40355947	40355948	40355949
Clear height, stationary	Clear height, stationary	Clear height, stationary
1600 mm	1810 mm	2030 mm
Inclination	Inclination	Inclination
45 °	45 °	45 °
Number of treads	Number of treads	Number of treads
8	9	10
Overall span	Overall span	Overall span
4151 mm	4571 mm	5011 mm
Tread width	Tread width	Tread width
800 mm	800 mm	800 mm
SKU	SKU	SKU
40355950	40355953	40355954
Clear height, stationary	Clear height, stationary	Clear height, stationary
2240 mm	740 mm	950 mm



Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 11	Number of treads 4	Number of treads 5
Overall span 5431 mm	Overall span 2431 mm	Overall span 2851 mm
Tread width 800 mm	Tread width 1000 mm	Tread width 1000 mm
SKU 40355955	SKU 40355956	SKU 40355957
Clear height, stationary 1170 mm	Clear height, stationary 1380 mm	Clear height, stationary 1600 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 6	Number of treads 7	Number of treads 8
Overall span 3291 mm	Overall span 3711 mm	Overall span 4151 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
SKU 40355958	SKU 40355959	SKU 40355960
Clear height, stationary 1810 mm	Clear height, stationary 2030 mm	Clear height, stationary 2240 mm




Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 9	Number of treads 10	Number of treads 11
Overall span 4571 mm	Overall span 5011 mm	Overall span 5431 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
SKU 40355903	SKU 40355904	SKU 40355905
Clear height, stationary 880 mm	Clear height, stationary 1130 mm	Clear height, stationary 1380 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 4	Number of treads 5	Number of treads 6
Overall span 1915 mm	Overall span 2203 mm	Overall span 2492 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
SKU 40355906	SKU 40355907	SKU 40355908
Clear height, stationary 1630 mm	Clear height, stationary 1880 mm	Clear height, stationary 2130 mm
Inclination	Inclination	Inclination




60 °	60 °	60 °
Number of treads	Number of treads	Number of treads
7	8	9
Overall span	Overall span	Overall span
2781 mm	3069 mm	3358 mm
Tread width	Tread width	Tread width
600 mm	600 mm	600 mm
SKU	SKU	SKU
40355909	40355910	40355913
Clear height, stationary	Clear height, stationary	Clear height, stationary
2380 mm	2630 mm	880 mm
Inclination	Inclination	Inclination
60 °	60 °	60 °
Number of treads	Number of treads	Number of treads
10	11	4
Overall span	Overall span	Overall span
3647 mm	3935 mm	1915 mm
Tread width	Tread width	Tread width
600 mm	600 mm	800 mm
SKU	SKU	SKU
40355914	40355915	40355916
Clear height, stationary	Clear height, stationary	Clear height, stationary
1130 mm	1380 mm	1630 mm
Inclination	Inclination	Inclination
60 °	60 °	60 °



Number of treads 5	Number of treads 6	Number of treads 7
Overall span 2203 mm	Overall span 2492 mm	Overall span 2781 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
SKU 40355917	SKU 40355918	SKU 40355919
Clear height, stationary 1880 mm	Clear height, stationary 2130 mm	Clear height, stationary 2380 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 8	Number of treads 9	Number of treads 10
Overall span 3069 mm	Overall span 3358 mm	Overall span 3647 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
SKU 40355920	SKU 40355923	SKU 40355924
Clear height, stationary 2630 mm	Clear height, stationary 880 mm	Clear height, stationary 1130 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °



Number of treads 11	Number of treads 4	Number of treads 5
Overall span 3935 mm	Overall span 1915 mm	Overall span 2203 mm
Tread width 800 mm	Tread width 1000 mm	Tread width 1000 mm
SKU 40355925	SKU 40355926	SKU 40355927
Clear height, stationary 1380 mm	Clear height, stationary 1630 mm	Clear height, stationary 1880 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 6	Number of treads 7	Number of treads 8
Overall span 2492 mm	Overall span 2781 mm	Overall span 3069 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
SKU 40355928	SKU 40355929	SKU 40355930
Clear height, stationary 2130 mm	Clear height, stationary 2380 mm	Clear height, stationary 2630 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads	Number of treads	Number of treads



9	10	11
Overall span	Overall span	Overall span
3358 mm	3647 mm	3935 mm
Tread width	Tread width	Tread width
1000 mm	1000 mm	1000 mm