



W 170 trolley

The all-rounder: a sturdy box trolley for universal applications, for in-company logistics or for the transportation of waste.

Product description

- Robust and durable due to many quality features, e.g. sturdy, generously dimensioned edge and base profile, permanent connection to jacket and base plate using high-strength positive locking, riveted shell joint and welded frame profiles.
- High stiffness due to end and side walls reinforced with peripheral beading and corner beads.
- Effortless to manoeuvre due to easy-running, non-marking rubber wheels that are mounted on roller bearings and equipped with thread guards.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- End and side walls reinforced with peripheral beading and corner beads.
- Running gear: 2 swivel and 2 fixed castors, corner-mounted, Ø 125 mm, 40 mm wide, easy running, rubber wheels, “non-marking”, roller bearings, thread guards.
- Casing joint riveted throughout. Frame profile sections welded.



Product features

Chassis arrangement can be changed Yes	Corner beading Yes	Formation Chassis 2 swivel and 2 fixed castors mounted at the corners	Material Aluminium	Peripheral beading Yes
Wheel diameter 125 mm	Wheel diameter 40 mm			



Product variants

SKU 40631	SKU 40635
Internal dimensions L x W x H 1.000 mm x 640 mm x 650 mm	Internal dimensions L x W x H 1.250 mm x 700 mm x 750 mm
Outside dimensions max. L x W x H 1.050 mm x 690 mm x 855 mm	Outside dimensions max. L x W x H 1.300 mm x 750 mm x 955 mm
Volume 415 l	Volume 655 l
Weight 19.5 kg	Weight 23.7 kg