



W 172 transport trolley


Sturdy aluminium trolley for versatile use.

Product description

- Sturdy aluminium trolley for a wide variety of applications.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to side walls and base.
- One of the long sides has a cut-out section measuring approx. 1,230 x 295 mm for convenient loading and unloading.
- End and side walls reinforced with peripheral beading and corner beads.
- One ergonomic handle at either end.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- One long side with cutout section, approx. 1,230 x 295 mm.
- Container cutout with profile-section surround; profile-section joints continuously welded.
- Chassis: 2 swivel and 2 fixed castors, corner-mounted, Ø 200 mm, 40 mm wide; easy-running, non-marking rubber wheels with roller bearings and thread guards.



Product features



Formation Chassis 2 swivel and 2 fixed castors mounted at the corners	Internal dimensions L x W x H 1.500 mm × 900 mm × 700 mm	Material aluminium	Outside dimensions max. L x W x H 1.650 mm × 950 mm × 980 mm	Peripheral beading Yes
Volume 945 l	Weight 37 kg	Wheel diameter 200 mm		

Product variants