



Single-axle fuelling platform fuelling equipment

This manoeuvrable single-axle fuelling platform facilitates the safe and comfortable refuelling of aeroplanes and helicopters.

Product description

- Improved manoeuvrability (small turning radius) thanks to single-axle chassis.
- Platform height: 1.50 metres
- This product can be ordered with towing eye or ball coupling on its tow bar depending on the towing vehicle used.
- A platform (500 x 850 mm) optimised for secure footing offers enough space for refuelling to be performed ergonomically.
- The treads and platform are fitted with R13 anti-slip safety panels that allow water to drain easily, offering an extremely high level of safety.
- The 415 mm pneumatic tyres in combination with a tow bar allow for towing speeds of up to 30 km/h.
- Our platforms comply with the European standards EN 12312-5 and EN 1915-1.

Hints and special features

No fuelling equipment is included for this product variant. However, the same product is also available with fuelling equipment, either already or not yet primed.





Standards used: DIN EN 1915 - General requirements
Part 1 - Basic safety requirements
Part 2 - Stability and strength requirements
DIN EN 12312 - Aircraft ground support equipment
Part 5 - Aircraft fuelling equipment
Part 8 - Maintenance stairs and platforms

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.
Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 29/3/2026
Subject to change or error.