



# Fuelling platform with height adjustable between 1.90 and 3.20 metres.

The fuelling platform equipped with hydraulic height adjustment offers you flexible access to fuelling stations at various heights.

## Product description

- Hydraulic height adjustment between 1.90 and 3.20 metres.
- This product can be ordered with towing eye or ball coupling on its tow bar depending on the towing vehicle used.
- A platform (918 x 830 mm) optimised for secure footing offers enough space for refuelling to be performed ergonomically.
- The treads and platform are fitted with R13 anti-slip safety panels that allow water to drain easily, offering an extremely high level of safety.
- The 530 mm pneumatic tyres in combination with a tow bar allow for towing speeds of up to 30 km/h.
- Our platforms comply with the European standards EN 12312-5 and EN 1915-1.



## Hints and special features

No fuelling equipment is included for this product variant. However, the same product is also available with fuelling equipment.

Standards used: DIN EN 1915 - General

requirementsPart 1 - Basic safety requirementsPart 2 -



Stability and strength requirementsDIN EN 12312 -  
Aircraft ground support equipmentPart 5 - Aircraft  
fuelling equipmentPart 8 - Maintenance stairs and  
platforms

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 24/6/2026  
Subject to change or error.